B-]-A	Power Sup USA/Canada	ply Cords - Anschlußleitungen		05	520 01
Document	Catalog No. / Katalog-Nr.	Description / Beschreibung			U/M EDP-No.
7302 7403 8121	3 Conductor Line 523 BLK 514 BLK 3020 GRY 3011 GRY	Cords, Types SVT PVC and SJT PVC, 125 Volts, 60°C, Jack Line Cord, SVT 18/3 (0.82mm ²), 2.3m, Cord Ø 6.4mm, Black, 10A Line Cord, SJT 16/3 (1.31mm ²), 3.0m, Cord Ø 8.9mm, Black, 13A Line Cord, SJT 18/3 (0.82mm ²), 2.5m, Cord Ø 8.3mm, Gray, 10A Line Cord, SJT 18/3 (0.82mm ²), 2.5m, Cord Ø 8.3mm, Gray, 10A	ket Color 154g 324g 250g 250g	25 25 100 100	c or Gray ea 107142 ea 107145 ea 100621 ea 100618
523		3 conductor line cords types SVT and SJT, 125 Volts, 60°C, Jacket color: Black or Gray. One end with C-13 style connector - other end stripped. UL listed and CSA certified. Used for buisiness machines, point-of-sale terminals, computers and peripheral equipment or OEM equipment. Further items and informations can be found in documents indicated.			
1866		ower Tool Replacement Cord, Type SJTW PVC (Outdoor Lis			
(J.)	03024 BLK (C2119/8)	Replacement Cord, SJTW 16/2, 2.4m, Cord Ø 7.9mm, Black, 13A	198g	50/5	ea 110043
		Appliance and power tool replacement cord, 13A, polarized plug NEMA 1-15P, 125 Volts, 1625 Watts, SJTW 16/2, cord length 8ft (2.44m), black jacket. For use with double insulated equipment, major and small appliances, motors, and power tools, UL listed.			
		Further items and informations can be found in documents indicated.			
7302 7401 5351	3 Conductor Jack	teted Power Supply Cords, Type SJT PVC, 125 Volts, 60°C,	Jacket C	olor: E	Black
	501 BLK	Power Cord, SJT 18/3 (0.82mm ²), 2.0m, Cord Ø 8.3mm, Black, 10A	180g	25	ea 107685
	503 BLK 505 BLK	Power Cord, SJT 16/3 (1.31mm ²), 2.0m, Cord Ø 8.9mm, Black, 13A Power Cord, SJT 14/3 (2.08mm ²), 2.0m, Cord Ø 9.6mm, Black, 15A	226g 304g	25 25	ea 107689 ea 106876
	506 BLK	Power Cord, SJT 14/3 (2.08mm ²), 3.0m, Cord Ø 9.6mm, Black, 15A	430g	25	ea 107498
		Power supply cords types SJT PVC, 125 Volts, 60°C, jacket color: black. One end with NEMA 5-15P plug 125V - other end stripped (38.1mm/15.9mm). UL listed and CSA certified. Used for buisiness machines, point-of-sale terminals, computers and peripheral equipment or OEM equipment. Further items and informations can be found in documents indicated.			
2006 7302	3 Conductor Jack	teted Power Supply Cords, Type SJ Rubber, 125 Volts, 60°C	C. Jacket	Color	Black
	778 BLK	Power Cord, SJ 18/3 (0.81mm ²), 2.4m, Cord Ø 8.4mm, Black, 10A	221g	25	ea 107674
	783 BLK 789 BLK	Power Cord, SJ 16/3 (1.31mm ²), 2.7m, Cord Ø 8.9mm, Black, 13A Power Cord, SJ 14/3 (2.08mm ²), 4.6m, Cord Ø 9.6mm, Black, 15A	308g 665g	25 25	ea 107677 ea 107680
		3 conductor power supply cords types SJ rubber, 125 Volts, 60°C, jacket color: black. One end with NEMA 5-15P plug 125V - other end stripped (38.1mm/15.9mm). UL listed and CSA certified. Used for buisiness machines, point-of-sale terminals, computers and peripheral equipment or OEM equipment. Further items and informations can be found in documents indicated.			
1679 7302 1383	3 Conductor Pow	er Cords, Types SVT PVC and SJT PVC, 125 Volts, 60°C, Ja	icket Col	or: Bla	ick
	531 BLK 535 BLK 532 BLK 534 BLK	Power Cord, SJT 18/3 (0.82mm ²), 2.0m, Cord Ø 8.3mm, Black, 10A Power Cord, SVT 18/3 (0.82mm ²), 2.3m, Cord Ø 6.4mm, Black, 10A Power Cord, SJT 18/3 (0.82mm ²), 3.0m, Cord Ø 8.3mm, Black, 10A Power Cord, SJT 16/3 (1.31mm ²), 3.0m, Cord Ø 9.0mm, Black, 13A	192g 180g 276g 345g	25 25 25 25	ea 107294 ea 107293 ea 107295 ea 107255
A DE DE		3 conductor power supply cords types SVT and SJT, 125 Volts, 60°C, jacket color: Black. One end with NEMA 5-15P plug 125V - other end with C-13 straight connector. UL listed and CSA certified. Used for buisiness machines, point-of-sale terminals, computers and peripheral equipment or OEM equipment. Further items and infos in documents indicated.			
1384 7302 7402	3 Conductor Jack	teted Power Supply Cords, Type SJT PVC, 125 Volts, 60°C,	Jacket C	olor: E	Black
	537 BLK 540 BLK	Power Cord, SJT 18/3 (0.82mm ²), 2.0m, Cord Ø 8.3mm, Black, 10A Power Cord, SJT 16/3 (1.31mm ²), 3.0m, Cord Ø 9.0mm, Black, 13A	192g 345g	25 25	ea 113358 ea 114732
	040 BLIN	3 conductor power supply cords types SJT, 125 Volts, 60°C, jacket color: Black. One end with NEMA 5-15P plug 125V - other end with C-13 right angle connector. UL listed and CSA certified. Used for buisiness machines, point-of-sale terminals, computers and peripheral equipment or OEM equipment.	e log		
		Further items and informations can be found in documents indicated.			
1680 7302	3 Conductor Spec	cial Power Cords, Type SVT PVC, 125 Volts, 60°C, Jacket C	olor: Bla	ck or (Frav
	543 BLK	Power Cords, Type SVT PVC, 125 Volts, 60 C, Jacket C Power Cord, SVT 18/3 (0.82mm ²), 2.3m, Cord Ø 6.4mm, Black, 7A	166g	25	ea 107262
	543 GRY	Power Cord, SVT 18/3 (0.82mm ²), 2.3m, Cord Ø 6.4mm, Gray, 7A 3 conductor special power supply cords types SVT PVC, 125 Volts, 60°C, jacket color: Black or Gray. One end with NEMA 5-15P plug 125V - other end with special oval connector	166g	25	ea 107263
		(please refer to document #1680 for dimensions). UL listed and CSA certified. Used for buisiness machines, point-of-sale terminals, computers and peripheral equipment or OEM equipment.			
4004 7000 7074		Further informations can be found in documents indicated.			
<u>1681 7302 5351</u>	Extension Cord S 633 BLK	Ets, Type SJ Rubber or Type SJT PVC, 125 Volts, 60°C, Jac Extension Cord, SJ 16/3 (1.32mm ²), 3.0m, Cord Ø 8.9mm, Black, 13A	376g	25	ea 107168
	640 BLK 02180 BLK (A2316/8)	Extension Cord, SJ 16/3 (1.32mm ²), 4.6m, Cord Ø 8.9mm, Black, 13A Extension Cord, SJT 16/3 (1.31mm ²), 2.4m, Cord Ø 8.4mm, Black, 13A	573g 286g	10 50	ea 107169 ea 102141
	02182 BLK (A2316/15)	Extension Cord, SJT 16/3 (1.31mm ²), 4.6m, Cord Ø 8.4mm, Black, 13A	520g	30	ea 104678
- AL		3 conductor extension cord sets, type SJ rubber or type SJT PVC, 125 Volts, 60°C, jacket color: Black. One end with NEMA 5-15P plug 125V - other end with NEMA 5-15R connector 125V. UL listed, CSA certified where applicable. Further items and informations can be found in documents indicated.			
Lagerstr. 1 Fax	+49-6151-8786-22 ht	Iternet Homepage: Weitere Typen auf Anfrage. Further items on red tp://www.BiaGmbH.com Änderungen vorbehalten. Dimensions mm. St mail: info@BiaGmbH.com Abmessungen in mm. to change without n	ibject		05.04.2001