

Maxim

The Ultimate in Lightbar Versatility

Height: 140mm (5.5") Width: 330mm (13") Length: up to 2540mm (100")





Optional bespoke lettering and logo's available for all Premier Hazard lightbar illuminated centre sections.



Maxim

Available Options

Available Lengths: 255mm (10"), 390mm (15"), 510mm (20"), 630mm (25"), 750mm (30"), 870mm (34"), 990mm (39"), 1110mm (44"), 1230mm (48"), 1350mm (53"), 1470mm (58"), 1590 (63"), 1710mm (67"), 1830mm (72"), 1950mm (77"), 2070mm (82"), 2190mm (86"), 2310mm (91"), 2540mm (100")

Available Colours:



Rotator Assemblies

- 12 / 24v Rotator Dual Voltage Rotator
- 12 / 24v Rotary 12 / 24v Oscilasers
- Synchronised rotators to suit ECE65
- Airport rotator 12v motor 24v bulb

Halogen Warning

- Small alternating lights
- Large alternating lights

Strobe Heads

- 360 degree Strobe Double Flash 12/24v
- Large Linear Strobe Small Linear Strobe
- Large Rectangular Strobe
- Small Rectangular Strobe
- Round Strobe

Strobe Power Supply

- 2 output 40 watt supply
- 2 / 4 output 60 watt supply
- 2 / 4 output 75 watt supply
- o 2 / 4 / 6 output 75 watt supply
- o 2 / 4 / 6 output 90 watt supply

Signs & Grilles

- Centre sign
- Flashing STOP sign
- Speaker Grille

LED's

- LEDX 12/24v single head LED's
- 360 degree LED's
- PH34 LED directional light
- PH46 LED directional light

Infosigns

- 45mm 1 / 2 message or police messages only
- 60mm 2 / 3 message or police messages only
- 75mm 3 / 10 message or any messages required
- o 90mm 10 / 30 / 99 message or police messages required
- 90mm programmable software available

Speakers

- 60 Watt
- 100 Watt

Spot / Flood Lighting

- 2 / 4 Alley Lights
- Spot / Flood Lights

Camera Bracket

• Bracket kit for mounting ANPR camera

Roof Connector

• 15 metres of cable with male and female connections