



UL CSA  
ANSI Std. C78.180  
ETL Certified

Starter für Leuchtstoffröhren, mit feuchtigkeitsbeständigem Keramik-Kondensator, universell einsetzbar

Fluorescent Lamp Starter, w/Humidity Resistant Ceramic Condenser  
Used for all Basic Applications

Catalog No.	Ref. ID. No.	Description	Lamp Size	Prongs	UPE/Pack
13886	FS-2	Basic Type	14, 15 & 20 Watt	2	100/10
13891	FS-4	Basic Type	13, 30 & 40 Watt	2	100/10
13894	FS-5	Basic Type	4, 6 & 8 Watt	2	100/10
13885	FS-12	Basic Type	32 Watt Circline	2	100/10
13889	FS-25	Basic Type	25W & 22W Circline	2	100/10
13895	FS-85	Basic Type	85, 90 & 100 Watt	2	50/10
13888	FS-20	Manual Reset	15 & 20 Watt	2	100/10
13890	FS-30	Manual Reset	30 Watt	2	100/10
13893	FS-40/400	Manual Reset	40 Watt	2	100/10
13898	FS-850	Manual Reset	90 & 100 Watt	4	on Reqst
13892	FS-4-NA	Automatic Reset	40 Watt	2	100/10
13897	FS-85-NA-4	Automatic Reset	90 & 100 Watt	4	on Reqst