


Standard-Leuchtröhren
(Starter erforderlich)

USA/CDN STANDARD FLUORESCENT LAMPS
(Starter Required)
PREHEAT



Standard preheat fluorescent lamps are used in warehouses, factories, corridors, workshops, some offices and are general purpose industrial use. Standard lamps are available from 13 to 40 Watt, have a T8 or T12 tube (25.4mm or 38.1mm dia) and G13 medium BiPin base.

NOTE: Preheat fluorescent lamps require use of starters.

Watt	Lamp Ref. / Base	Description	Length/Diam.	Cat.No.	Wgt. ea	UPE/Pack	EDP No
13	F13T8/CW	G13 Cool White	304.8	21766	61g	24	D 100258
14	F14T8/CW	G13 Cool White	381.0	21486	64g	24	D 100272
15	F15T8/CG	G13 Cool Green	457.2	21708	88g	24	D 100284
15	F15T8/CW	G13 Cool White	457.2	21616	88g	24	C 100274
15	F15T8/WW	G13 Warm White	457.2	21701	88g	24	D 100279
14	F14T12/CW	G13 Cool White	381.0	21409	120g	30	D 104461
14	F14T12/WW	G13 Warm White	381.0	21435	120g	30	D 104462
15	F15T12/CW	G13 Cool White	457.2	21532	130g	30	D 104465
15	F15T12/WW	G13 Warm White	457.2	21542	130g	30	D 104466