


Standard-Leuchtröhren  
(Starter erforderlich)

USA/CDN STANDARD FLUORESCENT LAMPS  
(Starter Required)  
PREHEAT



Standard preheat fluorescent lamps are used in warehouses, factories, corridors, workshops, some offices and are general purpose industrial use. Standard lamps are available from 13 to 40 Watt, have a T8 or T12 tube (25.4mm or 38.1mm dia) and G13 medium BiPin base.

NOTE: Preheat fluorescent lamps require use of starters.

Watt	Lamp Ref. / Base	Description	Length/Diam.	Cat.No.	Wgt. ea	UPE/Pack	EDP No
22	F22T8/CW	G13 Cool White	660.4 $\varnothing$ 25.4	23026	140g	24 D	100346
25	F25T12/CW/28	G13 Cool White	711.2 $\varnothing$ 38.1	22527	220g	30 D	104470
25	F25T12/CW/30	G13 Cool White	762.0 $\varnothing$ 38.1	22528	240g	30 D	104471
25	F25T12/WW/30	G13 Warm White	762.0 $\varnothing$ 38.1	22333	240g	30 D	112904
25	F25T12/CW/33	G13 Cool White	838.2 $\varnothing$ 38.1	22529	260g	30 D	104472
30	F30T8/CW	G13 Cool White	914.4 $\varnothing$ 25.4	23116	150g	24 C	100365
30	F30T8/CWX	G13 CW Deluxe	914.4 $\varnothing$ 25.4	23127	150g	24 D	112902
30	F30T8/WW	G13 Warm White	914.4 $\varnothing$ 25.4	23701	150g	24 D	100406
40	F40T12/CW/LT	G13 Cool White	1219.2 $\varnothing$ 38.1	24019	380g	30 C	104474