



Industrial AC Switches

Dimensions refer to all switches listed.

Meets all requirements for NEMA WD-1, ANSI. UL Listed (File #E-7458) to meet the latest Federal Specification, WS-896. CSA Certified (File #LR-3413).

NOM (Mexico) Certified (#057). Environmental: Flammability, Rated U2.

Operating Temperature: -40°C to 65°C. Further switches available upon request.

Catalog No.	Ampere	Description		Color*	UPE/Pack	Wght/ea	EDP-No
1101-2I	15	Single-Pole	1xAus	Ivory	100/10	61g	113997
1102-2I	15	Double-Pole	2xAus	Ivory	20/10	68g	113998
1103-2I	15	3-Way	1xWechsel	Ivory	50/10	64g	113999
1104-2I	15	4-Way	1xKreuz	Ivory	20/10	68g	114000
1121-2I	20	Single-Pole	1xAus	Ivory	50/10	61g	114001
1122-2I	20	Double-Pole	2xAus	Ivory	20/10	68g	113992
1123-2I	20	3-Way	1xWechsel	Ivory	20/10	64g	114002
1124-2I	20	4-Way	1xKreuz	Ivory	20/10	68g	114003

*Colors: Available in Brown, White, Gray, Red, Black upon request.