



UL CSA■

| |
|---|
| Use Liquidtight Flex Metallic or Type "B" Nonmetallic Conduit |
|---|

Liquidtight Connectors
with Locknut, Steel/
Malleable Iron

Schlauchverschraubung, Stahl/Guß, mit Gegenmutter UE=UPE/Packed

| Nom. | CatNo | UE | # 90° | UE | # 45° | UE | A | B | C | D | E | F | G | NPT Holeø |
|------|-------|----|-------|----|-------|----|----|----|----|----|----|----|----|-----------|
| 3/8 | 3511■ | 25 | 3541■ | 25 | 3561■ | 25 | 27 | 15 | 37 | 30 | 33 | 33 | 37 | 21.8-23.0 |
| 1/2 | 3512■ | 50 | 3542■ | 25 | 3562■ | 25 | 27 | 15 | 37 | 30 | 33 | 33 | 37 | 21.8-23.0 |
| 3/4 | 3513■ | 25 | 3543■ | 25 | 3563■ | 25 | 35 | 15 | 40 | 30 | 37 | 37 | 41 | 27.8-29.0 |
| 1 | 3514■ | 10 | 3544■ | 10 | 3564■ | 10 | 43 | 17 | 43 | 35 | 39 | 45 | 56 | 34.5-35.7 |
| 1 ¼ | 3515■ | 10 | 3545■ | 10 | 3565■ | 10 | 53 | 16 | 52 | 36 | 43 | 50 | 64 | 43.7-44.9 |
| 1 ½ | 3516■ | 5 | 3546■ | 5 | 3566■ | 5 | 61 | 16 | 56 | 42 | 51 | 56 | 68 | 50.0-51.2 |
| 2 | 3518■ | 5 | 3548■ | 5 | 3568■ | 5 | 73 | 17 | 58 | 43 | 57 | 64 | 83 | 62.3-63.5 |