



UL Listed  
File # E14814



Size	A	B	C	D	E
3/8	54.8	15.1	29.4	31.8	51.6
1/2	65.9	15.1	33.3	32.5	60.3
3/4	65.9	15.1	41.3	36.5	63.5
1	73.0	18.3	49.2	44.5	69.9
1 1/4	86.5	19.1	61.1	50.0	88.1
1 1/2	87.3	19.1	70.6	57.2	91.3
2	100.8	19.1	85.7	64.3	111.9

Size refer to Type  
"CN" or "LNM"  
Flexible Conduit

Dimensions = mm

Liquidtight "STNM" Flexible Nonmetallic Conduit Connectors  
for Use with Type "CN" or "LNM" Flexible Nonmetallic Conduit

Cat# Straight	Size	Kg/1000	UPE/Pack
STNM-38	3/8"	102	100/25
STNM-50	1/2"	147	100/25
STNM-75	3/4"	201	50/25
STNM-100	1"	291	25/5
STNM-125	1 1/4"	540	25/5
STNM-150	1 1/2"	685	10/2
STNM-200	2"	1076	5/1

Cat. No. 90°	Size	Kg/1000	UPE/Pack
STNM-9038	3/8"	135	50/25
STNM-9050	1/2"	173	50/25
STNM-9075	3/4"	247	50/10
STNM-90100	1"	370	25/5
STNM-90125	1 1/4"	695	25/5
STNM-90150	1 1/2"	914	10/2
STNM-90200	2"	1416	5/1

STNM-SR38	3/8"	25	20/5
STNM-SR50	1/2"	53	20/5
STNM-SR75	3/4"	73	20/5
STNM-SR100	1"	85	20/5
STNM-SR125	1 1/4"	97	10/2
STNM-SR150	1 1/2"	121	10/2
STNM-SR200	2"	146	5/1

#### Wire Mesh Strain Relief

The "STNM-SR" Series with cap can be substituted for and related trade size "STNM" Series cap to convert it to a connector with a wire mesh strain relief.