



Rated for continuous
use at -20°C to $+105^{\circ}\text{C}$.



UL Listed (used with STNM Connectors)

TYPE "A" - FLEXIBLE PVC CONDUIT

Dimensions = mm

LISTED by Underwriter's Laboratories, Type LNM-P offers outstanding protection for vibration and constant flexure applications. A non-metallic, liquid-tight conduit that contains a core and jacket of poly-vinyl chloride, Type LNM-P is "crush proof" and conforms to the provisions of Article 351B of the NEC (R). Generally applicable temperature range from -20°C to $+105^{\circ}\text{C}$, intermitting to $+120^{\circ}\text{C}$. "Suitable for Outdoor"

Catalog Number	Size	Kg/km	UPE/Packed*	A	B	Min. Inside Bend Radius
LNM-P 10	3/8"	242	76m	19.4	12.5	63.5
LNM-P 11	1/2"	318	60m	23.4	16.1	76.2
LNM-P 12	3/4"	469	53m	29.5	21.1	101.6
LNM-P 13	1"	636	30m	36.3	26.8	152.4
LNM-P 14	1 1/4"	923	30m	46.0	35.4	177.8
LNM-P 15	1 1/2"	1196	15m	52.4	40.3	203.2
LNM-P 16	2"	1816	15m	65.3	51.6	228.6

* Further put-up's available upon request.