


Type B Flex Conduit



6701 -
6708




4731 &
4735



4732 -
4734



4721 -
4728



Swivel Lok

UL Listed - Standard 1660 (conduit);
Standard 514B (fittings)
CSA Certified - C22.2 No. 18

Dimensions = mm (Nominal)

Trade Size	Conduit # Inner	Conduit # Outer	Bend Radius
3/8	12.4	17.8	50.8
1/2	16.0	21.1	76.2
3/4	21.1	26.4	101.6
1	26.7	33.0	127.0
1 1/4	35.6	41.9	160.0
1 1/2	40.4	47.8	190.5
2	51.6	59.9	254.0

Swivel Lok®
Swivel Lok, multi-position connector (sizes 1/2 to 1) twists from 0° to 90°, easing installation in difficult locations and eliminating need to stock other angle connectors.

Nonmetallic Liquidtight Conduit and Connectors Type B, Swivel Lok Multi-Position Connectors and 90 Degree Connectors for Type B Conduit

For use in dry or wet locations when the conduit and fittings are not subject to physical damage.

All gray nonmetallic construction ends metal fatigue and separation problems.

Use Type B conduit and fittings whenever flexibility is required for installation, operation or maintenance.

Size	Conduit/Pack		Straight/Pack		Swivel Lok/Pack		90° Connector/Pack	
	Conduit #	Length	Conduit #	Length	Conduit #	Length	Conduit #	Length
3/8	6701	30m	4721	25	--	--	4731	25
1/2	6702	30m	4722	25	4732	25	--	--
3/4	6703	30m	4723	25	4733	25	--	--
1	6704	30m	4724	10	4734	10	--	--
1 1/4	6705	30m	4725	10	--	--	4735	10
1 1/2	6706	15m	4726	5	--	--	--	--
2	6708	15m	4728	5	--	--	--	--