


General Purpose
Flexible Metal Conduit



UL E53253

NEC Article 350

CSA LL18858

Fed.Spec. WW-C-566C

REDUCED WALL FLEX CONDUIT

For use in industrial, commercial, institutional, and residential wiring applications. For dry locations only. Other available length upon request.

Metall-Schutzschlauch, flexibel, dünnwandig.
Andere Lieferlänge auf Anfrage.

Dimensions = mm

Nominal	Steel	UPE/Packed	Aluminum	UPE/Packed	A	B	BendRad
3/8	BR-10	3 x 15m	ABR-10	3 x 15m	14.9	9.8	50.8
1/2	BR-11	3 x 15m	ABR-11	3 x 15m	22.6	16.1	76.2
3/4	BR-12	3 x 15m	ABR-12	3 x 15m	27.3	20.9	101.6
1	BR-13	3 x 15m	ABR-13	3 x 15m	34.0	25.9	127.0
1 1/4	BR-14	2 x 15m	ABR-14	2 x 15m	40.4	32.4	158.8
1 1/2	BR-15	2 x 15m	ABR-15	2 x 15m	48.3	39.1	190.5
2	BR-16	2 x 15m	ABR-16	2 x 15m	61.0	51.8	254.0
2 1/2	BR-17	1 x 7m	ABR-17	1 x 7m	75.2	63.5	317.5
3	BR-18	1 x 7m	ABR-18	1 x 7m	87.9	76.2	381.0
3 1/2	BR-350	1 x 7m	ABR-350	1 x 7m	100.6	88.9	444.5
4	BR-19	1 x 7m	ABR-19	1 x 7m	113.3	101.6	508.0