



2101-2105 Straight  
Connector. Larger  
Sizes have  
2 Screws



45°

2221-  
2223


2221 Illustrated is  
Malleable Iron, Other  
Sizes are Die Cast Zinc

2201-2203

90° Connector

2205-2206 Fasten with

1 Screw, Larger Sizes have 2 Screws



UL 514B CSA■

Squeeze Connector,  
Malleable Iron or Die  
Cast Zinc (45°), used  
with Flexible Metal  
Conduit

(VE = UPE/Packed)

Quetschverschraubung für Metallschlauch, Stahl- /Zinkguß (45°)

Nom.	Cat.#	VE	Conduit ø	# 90°	VE	Conduit ø	# 45°	VE	Conduit ø
3/8	2101■	50	13.5-15.9	2201■	50	11.1-15.9	2221■	25	13.5-15.9
1/2	2102■	50	20.7-23.8	2202■	25	18.3-23.8	2222■	25	20.6-23.8
3/4	2103■	25	26.2-28.6	2203■	50	22.2-28.6	2223■	25	24.2-28.1
1	2104■	25	30.2-35.0	2204■	25	31.0-35.0	Connectors avail- able 3/8 to 3 Straight and 90°		
1 1/4	2105■	25	37.3-42.4	2205■	10	36.5-42.2			
1 1/2	2106■	25	45.3-50.0	2206■	5	42.1-50.0			
2	2108■	10	57.2-62.7	2208■	5	54.0-62.7			