

## Threaded Adapters

## NPT / PG



### Configuration

Adapter Nickel-Plated Brass  
 External Thread NPT  
 Internal Thread PG as per DIN 40430

### Properties

Adapter from NPT to PG-threaded holes.  
 Temperature Range up to +200°C  
 Protection Grade Dependent on the combination with other components.

	Catalog Number	Former Cat. No.	AG	IG	GL mm	H mm	SW mm
	<b>531.3907.40</b>	538007	3/8 NPT	PG 7	13	21	19
	<b>531.1909.40</b>	512009	1/2 NPT	PG 9	20	25	22
	<b>531.1911.40</b>	512011	1/2 NPT	PG 11	20	31	22
	<b>531.1913.40</b>	512135	1/2 NPT	PG 13.5	20	34	24
	<b>531.1916.40</b>	512016	1/2 NPT	PG 16	20	34	27
	<b>531.3513.40</b>	534135	3/4 NPT	PG 13.5	19	32	29
	<b>531.3516.40</b>	534016	3/4 NPT	PG 16	19	32	29
	<b>531.7521.40</b>	510021	1 NPT	PG 21	25	35	36
	<b>531.7629.40</b>	511429	1 1/4 NPT	PG 29	25	35	46
	<b>531.7736.40</b>	511236	1 1/2 NPT	PG 36	27	41	52
	<b>531.7848.40</b>	520048	2 NPT	PG 48	30	48	65