



600V AC / 250V DC Gewicht: 6.8Kg

UL

H = 279.5mm (11.00")

B = 152.5mm (6.00")

T = 103.1mm (4.06")

max Anschluß.Ø 300mm²

Terminal Lug Wire Size

1-500 MCM (Cu Or Al)

| Type | Nennstrom[A] Amp.Rat[A] | Kurzschlußschnellauslösung[A] AC Magnetic Trip Settings[A] | |
|----------|----------------------------|---|--|
| LAL36125 | 125 | 625 - 1250 | Nennausschaltvermögen Nominal Breaking Capacity 240V -> 42KA } ->UL+NEMA AB-1 480V -> 30KA } 600V -> 22KA } 380V -> 35KA } ->IEC 157-1, + 415V -> 30KA } BS 4752 |
| LAL36150 | 150 | 750 - 1500 | |
| LAL36175 | 175 | 875 - 1750 | |
| LAL36200 | 200 | 1000 - 2000 | |
| LAL36225 | 225 | 1125 - 2250 | |
| LAL36250 | 250 | 1250 - 2500 | |
| LAL36300 | 300 | 1500 - 3000 | |
| LAL36350 | 350 | 1750 - 3500 | |
| LAL36400 | 400 | 2000 - 4000 | |