



Dimension C = Nut Flats

UPE = Packed

Dimensions = mm



Abmessung C = SW (Schlüsselweite)

Schlauchverschraubung, mit Gegenmutter
für Edelstahlschlauch Serie UI-511

- (1) Stahl, verzinkt
- (2) Messing, vernickelt

Use Stainless Steel Conduit
Series UI-511

- (1) Steel, zinc-plated
- (2) Brass, nickel-plated and
two Perbunan N seals

Stainless Steel AISI 304, NPT, ISO, 45° & 90° available on 883.0... & 299.0...

Nominal	Conduit	CatNo (1)	A	B	C	InsideØ	CatNo (2)	A	B	C	Cable-Ø	UPE
PG 9	5/16	883.009.7	28	7	21	7.0	297.709.7	30	8	20	5.0-10.0	25
PG 11	3/8	299.011.7	37	16	26	10.0	297.711.7	38	8	24	5.0-10.0	25
PG 13.5	3/8	299.013.7	37	16	26	10.0	297.713.7	41	8	26	8.0-15.0	25
PG 16	1/2	299.016.7	37	16	29	14.5	297.716.7	42	8	28	8.0-15.0	25
PG 21	3/4	299.020.7	38	16	35	19.5	297.722.7	45	8	35	11.0-20.5	25
PG 29	1	299.026.7	41	19	42	24.0	297.725.7	47	10	43	18.0-26.0	5
PG 36	1 ¼	299.035.7	51	16	56	31.0	297.734.7	58	12	54	26.0-31.0	5
PG 48	2	299.050.7	64	18	76	49.0						1