



Straight-Thru Strain Relief Bushings



For Round
Cables



max. 105°C

UL 94V-2

Dimensions = mm



VDE* Test Report

Catalog Number	UL/CSA Description	Cable Ø Nominal	(Dimensions = mm)				EDP-No
			A	B	C	D max	
1060 SR	SR 2M-1	3.2 - 4.8	9.5	8.4	10.3	1.6	114285
1157 SR	SR 5MN-3	5.6 - 6.2	12.7	11.4	11.2	1.6	114284
1150 SR*	SR 5N-4	6.4 - 7.4	12.7 - 13.1	11.4	11.1	1.6	114282
1147 SR*	SR 5P-4	6.4 - 7.4	12.7 - 13.1	11.4	11.1	2.5	114281
1184 SR*	SR 6W-1	7.6	12.7	11.8	11.1	2.3	114278
1200 SR*	SR 6N3-4	8.3 - 9.1	15.9	14.0	14.7	1.6	114275
1214 SR*	SR 6L-1	7.6 - 9.1	15.9 - 17.4	14.0	17.5	4.0	114273
1240 SR	SR 7K-2	8.3 - 9.1	22.2	19.6	19.0	3.2	114272
1244 SR	SR 7N-2	9.1 - 10.9	19.0 - 19.8	16.8	19.0	1.6	114271
1250 SR	SR 7L-2	9.4 - 10.9	22.2	19.6	19.0	5.1	114268
1497 SR	SR 31-2	10.8 - 12.1	22.2	21.3	20.6	3.2	114267
1254 SR	SR 8N-1	13.5 - 15.3	22.2	21.3	20.8	1.6	114266
1260 SR	SR 8P-2	13.5 - 15.3	22.2	21.3	20.8	3.2	114265
1274 SR	SR 8L-1	13.5 - 15.3	22.2	21.3	20.6	4.8	114264
1287 SR	SR 9P-2	15.2 - 17.5	27.7 - 28.6	25.4	25.4	7.1	114263

Standard Color: Black - Further Colors and Items available on Request