

Water & Foam

**Manufactured and Tested to
ANSI/UL Standards
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED**

RUGGED

- ★ Polished Stainless Steel Cylinders
- ★ All Metal Valve Construction
- ★ Exclusive crevice free, butt welded cylinders

CLEAN

- ★ Leaves no powder residue

USER FRIENDLY

- ★ Maximum visibility during discharge
- ★ Novice friendly, easy to understand instructions
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range +40°F to 120°F)

Note: The Model 240 may be freeze protected to -40°F by adding a Model 506 Anti-Freeze charge

SPECIFICATIONS	WATER	AFFF FOAM	FFFP FOAM
Application	Hose and Nozzle	Hose and Spray Nozzle	Hose and Air Aspirated Nozzle
Model Number	240	254	250
UL Rating	2A	2A:10B	3A:20B
Capacity	2½ Gal.	6 Liter	2½ Gal.
Shipping Wt. (lbs.) (Empty)	7 ½	7 ½	11
Height (in.)	24 ½	19	24 ½
Width (in.)	9	8	9
Depth (Diam. - in.)	7	7	7
Range (Initial - ft.)	45 - 55	10 - 12	10 - 12
F. M. Approved	Yes		Yes
Discharge Time (sec.)	55	30	55
Standard Bracket		Wall	

Stored Pressure



Model 240



Model 254

**Model 252
250**

Model 240 utilizes the cooling, soaking and penetrating effect of a 45-55 ft. stream of WATER. The 55 sec. discharge time makes it very effective for inexperienced operators for use on Class A fires. Protect from freezing by adding the Model 506 Loaded Stream/Anti-freeze charge. In areas with a high level chloride content water it may be corrosion protected by using the Model 507 charge.

Model 254 AFFF FOAM unique 6 liter size fills many requirements for a lighter, more compact Class A:B extinguisher. Easy and effective application with the patented spray nozzle. Apply to Class B liquid spills to prevent ignition. Ideal for emergency first response vehicles.

Model 252 FFFP FOAM adds Class B fire fighting capability to the Class A effectiveness of this extinguisher. The *Alcohol Resistant* fire fighting agent is effective on fires in a wide variety of Class B materials such as alcohols, polar solvents, hydrocarbons and combinations such as gasohol. Apply to a non-ignited Class B liquid spill and it will seal the surface minimizing the chance of serious fire.

Model 250 AFFF FOAM Class A:B extinguisher. Easy and effective application with air aspirated nozzle. Apply to Class B liquid spills to prevent ignition. Ideal for emergency first response vehicles.

Available in a 33 Gal. FFFP Wheeled or Stationary unit.

5 YEAR WARRANTY

Wet Chemical „Class K“ - Kitchen Use Extinguisher

Meets NFPA-10 Class K Standard
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED

- ★ Polished Stainless Steel Cylinders
- ★ All Metal Valve Construction
- ★ Swivel connection on hose allows nozzle to be oriented for proper use
- ★ Nozzle grip design with 45° angle for easy “overhead” application
- ★ Low PH agent discharged as a fine mist helps prevent grease splash and re-flash while cooling the appliance
- ★ Precise extinguishing agent application - no dry chemical to clean up
- ★ Excellent for use on all cooking appliances including solid fuel charbroilers
- ★ Tested on commercial deep fat fryers to ANSI / UL 711 test protocol and safe to use on Class C fires
- ★ Class 2A rated to meet fire code occupancy hazard requirements
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range +40°F to 120°F)

SPECIFICATIONS	WET CHEMICAL	
Application	Hose and Spray Nozzle	
Agent	POTASSIUM ACETATE SOLUTION	
Model Number	B260	B262
U/L Rating	2A:K	
Capacity	6 liters	2½ gals.
Shipping Wt. (lbs.)	22½	33½
Height (in.)	19	24½
Width (in.)	9	
Depth (Diam. - in.)	7	
Range (ft.)	10 - 12	
Discharge Time (sec.)	53	107
Standard Bracket	Wall	

Stored Pressure

FACTORY CHARGED



Model B260

Model B262

U.L. Listed
2A:K



WET CHEMICAL extinguishers are the best restaurant kitchen appliance hand portable fire extinguishers you can purchase. Both have been tested and approved for the new Class K listing by UL specifically for restaurant kitchen hazards. They contain a special potassium acetate based, low PH agent developed for use in pre-engineered restaurant kitchen systems. The recent trend to more efficient cooking appliances and use of unsaturated cooking oils dictates the use of a hand portable fire extinguisher with greater fire fighting capacity and cooling effect to combat these very hot and difficult fires. Available in two sizes - 6 liter or 2½ gal. with attractive stainless steel cylinders and easy to use hose and spray application nozzle. The superior fire fighting capability of the Wet Chemical agent is placed exactly where you aim it with no chemical residue to clean up. The Models B260 and B262 are the ideal “KITCHEN USE” fire extinguishers. They supplement existing cooking equipment automatic system protection for an extra margin of safety.

5 YEAR WARRANTY

Water Mist

*Manufactured and Tested to ANSI/UL Standards
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED*

RUGGED

- ★ Painted Stainless Steel Cylinders
- ★ All Metal Valve Construction
- ★ Exclusive crevice free, butt welded cylinder

ENVIRONMENTALLY FRIENDLY

- ★ No O.D.P. (Ozone Depletion Potential)
- ★ No EPA phase out or restrictions
- ★ No global warming concerns
- ★ Non magnetic construction tested by an independent agency for use in MRI facilities

CLEAN

- ★ Non-toxic
- ★ Causes no respiratory problems
- ★ De-ionized water extinguishing agent (sold separately)
- ★ Antiseptic white paint finish (easy to clean)
- ★ No powder residue

USER FRIENDLY

- ★ Wand provides greatest operator safety
- ★ Maximum visibility during discharge
- ★ No electrical conductivity back to the operator
- ★ No thermal or static shock
- ★ Minimal training - simplest to use
- ★ Most economical agent available
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range +40°F to 120°F)

SPECIFICATIONS	WATER MIST	
Application	Hose and Wand	Hose and Wand
Agent	DE-IONIZED WATER	
Model Number	B270NM	B272NM
U/L Rating	2A:C	2A:C
Capacity (gals.)	1.8	2.5
Shipping Wt. (lbs.) (Empty)	7	8
Extinguisher Height (in.)	18½	24½
Height with Hose & Wand [Installed in Clips] (in.)	24½	27½
Width with Hose & Wand [Installed in Clips] (in.)	11	11
Depth (Diam. - in.)	7	7
Range (ft.)	10-12	10 - 12
Discharge Time (sec.)	72	80
Standard Bracket	NM Wall	NM Wall

Stored Pressure



B270NM

B272NM

NON-MAGNETIC



**Tested to ANSI/UL 711
for Class C Listing**

WATER MIST is the ultimate extinguisher for Class A fires and where a potential Class C (electrical) hazard exists. The fine spray from the unique misting nozzle provides safety from electrical shock, greatly enhances the cooling and soaking characteristics of the agent and reduces scattering of burning materials. The Water Mist extinguishers contain de-ionized water making them the best extinguishers for protection of hospital environments, valuable books and documents, telecommunication facilities and "clean room" manufacturing facilities. The Water Mist extinguishers are easy to use, maintain, and service.

5 YEAR WARRANTY

Halotron

*Manufactured and Tested to
ANSI/UL Standards
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED AND USCG APPROVED**

**FAA Approved Model Available
(Model B394TS)**

RUGGED

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction

ENVIRONMENTALLY ACCEPTABLE

- ★ EPA approved "Clean Agent" for Class A, B and C hazards
- ★ Low GWP (Global Warming Potential)
- ★ Low ODP (Ozone Depletion Potential)
- ★ Short Atmospheric Lifetime

CLEAN

- ★ Leaves no residue

USER FRIENDLY

- ★ Maximum visibility during discharge
- ★ No electrical conductivity back to the operator
- ★ No thermal or static shock
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -40°F to 120°F)

* Note: 5 lb., 11 lb. and 15 ½ lb. extinguishers are USCG approved with the bracket listed on the UL label.

SPECIFICATIONS	HALOTRON I					
	VALVES		ALUMINUM		BRASS, CHROME PLATED	
Size & Capacity (lbs.)	1.4	2½	5	5½	11	15½
Application	Nozzle				Hose & Nozzle	
Model Number	A384T	B385TS	B386T	B394TS	397	398
UL & ULC Rating	1B:C	2B:C	5B:C	5B:C	1A:10B:C	2A:10B:C
Shipping Weight (lbs.)	3¼	5¼	9¼	10	22½	27½
Height (in.)	10	15½	15¼	15	21 7/8	21 7/8
Width (in.)	3½	6 3/8	5¼	5 1/8	9¼	9¼
Depth (Diam. - in.)	2 5/8	3	4¼	4¼	6	6
Range (ft.)	6 - 8	6 - 10	9 - 15	9 - 15	9 - 15	12 - 18
Discharge Time (sec.)	9	9	9	9	9	14
Available with Chrome Plated Cylinder	Yes	Yes	Yes			
Minimum Space Requirement (cu. ft.)	196	350	700	770	1540	2170
Standard Bracket	Vehicle	Vehicle	Vehicle	Aircraft	Wall	Wall

Stored Pressure



**FAA Approved
(Model B394TS)**



**Models
397
398**

**Models
A384T
B385TS
B386T
B394TS**

HALOTRON I is a "Clean Agent" HydroChloroFluoroCarbon (HCFC) discharged as a rapidly evaporating liquid which leaves no residue. It effectively extinguishes Class A and B fires by cooling and smothering and it will not conduct electricity back to the operator. Halotron is pressurized with Argon gas and is an EPA and FAA approved agent suitable for use on Class A, B and C fires. It has a *low* GWP of 0.04 - 0.24, *low* ODP of 0.014 (twelve times lower than the EPA maximum allowable ODP of 0.20) and a *low* Atmospheric Lifetime (3½ to 11 years).

Halotron is intended for use in areas formerly protected by Halon 1211 hand portable extinguishers such as computer rooms, telecommunications facilities, clean rooms, data storage areas, offices (for protection of sensitive electronic equipment), boats and vehicles.

**AVAILABLE IN WHEELED EXTINGUISHERS
5 YEAR WARRANTY**

Haloon 1211

Manufactured and Tested to ANSI/UL Standards
 ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED AND USCG APPROVED*

RUGGED

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction

CLEAN

- ★ Leaves no residue
- ★ Reclaimed Halon 1211 is Restored to Original Military Specification
- ★ Uses All Recycled Gas in Accordance With The Montreal Protocol

USER FRIENDLY

- ★ Maximum Visibility During Discharge
- ★ No Electrical Conductivity Back to the Operator
- ★ No Thermal or Static Shock
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -65°F to 120°F)

* All extinguishers USCG approved except model A344T

Stored Pressure



Models
 B369
 B371
 361

Models
 A344T
 C352TS
 C354TS
 B355T

SPECIFICATIONS		HALON 1211		
VALVES		CHROME PLATED BRASS		
Size & Capacity (lbs.)		9	13	17
Application		Hose		
Model Number		B369	B371	361
UL Rating		1A:10B:C	2A:40B:C	4A:80B:C
Shipping Weight (lbs.)		16¼	22	36¼
Height (in.)		16¼	20¼	23 7/8
Width (in.)		8½	8½	9¼
Depth (Diam. - in.)		5	5	7
Range (ft.)		12-18	12-18	12-18
Discharge Time (sec.)		9	14	22
Minimum Space Requirement (cu. ft.)		1123	1622	2120
Standard Bracket		Wall	Wall	Wall

SPECIFICATIONS		HALON 1211			
VALVES		ALUMINUM			
Size & Capacity (lbs.)		1¼	2½	3	5
Application		Nozzle		Hose	
Model Number		A344T	* C352TS	* C354TS	B355T
UL Rating		2B:C	5B:C	5B:C	10B:C
Shipping Weight (lbs.)		2¼	5½	6	9¼
Height (in.)		10	14 3/8	14 3/8	15¼
Width (in.)		3 5/8	4½	6	5¼
Depth (Diam. - in.)		2 5/8	3	3	4¼
Range (ft.)		9-12	9-15	9-15	9-15
Discharge Time (sec.)		10	10	12	10
Minimum Space Requirements (cu. ft.)		156	312	375	624
Standard Bracket		Vehicle	Aircraft	Aircraft	Veh/Marine

* Modified valve

HALON 1211 is a liquified gas, pressurized with nitrogen, which discharges as a vapor causing no cold or static shock and no impairment of the operator's vision. This "CLEAN" agent quickly penetrates difficult to see and hard to reach areas and leaves no residue. **It is recommended for protection of delicate, sensitive and expensive computers, electrical equipment, tapes and film, automotive and aircraft engines, laboratory chemicals and equipment.**

Quality industrial grade hardware, "CLEAN" agent, light weight, good discharge range and excellent fire extinguishing ability.

1 YEAR WARRANTY

Carbon Dioxide

*Manufactured and Tested to
ANSI/UL Standards
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED, FM AND USCG APPROVED*

- ★ Rust free aluminum cylinders - up to 30% lighter than steel cylinders
- ★ All Metal Valve Construction
- ★ Meets many hospital medical equipment requirements
- ★ Independently tested and approved for use in MRI facilities (Model 322NM)
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -40°F to 120°F)

Note: All extinguishers are USCG approved with bracket listed on UL label

SPECIFICATIONS	CARBON DIOXIDE			
	5	10	15	20
Size & Capacity (lbs.)	5	10	15	20
Application	Horn	Hose & Horn		
Model Number	322	330	331	332
UL Rating	5B:C	10B:C	10B:C	10B:C
Shipping Weight (lbs.)	14	28¼	37¼	50¼
Height (in.)	17¾	24	30	30
Width (in.)	8¼	12	12	13
Depth (Diam. - in.)	5¼	7	7	8
Range (ft.)	3- 8			
Discharge Time (sec.)	10	10	12½	19
F. M. Approved	Yes			
Standard Bracket	Wall			



Carbon Dioxide is discharged as a white cloud of "snow" which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.

Also available in 50 / 100 lb. wheeled extinguishers and 100 lb. stationary.

5 YEAR WARRANTY

Class D

*Manufactured and Tested to ANSI/UL Standards
ISO-9001:2000/ISO-14001:2004 Certified
FM APPROVED*

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction
- ★ Unique "soft flow" extension applicator plus built in long range nozzle
- ★ Special corrosion resistant yellow (Class D) color coded paint finish
- ★ F.M. listed (TO ANSI/UL 299 and ANSI/UL 711)
- ★ Bar Coded and Bi-lingual Labels

The "soft flow" extension applicator is particularly suited for fighting Class D fires. It keeps the operator's hands away from the extreme heat and prevents inhalation of toxic fumes caused by burning material. The easily controlled, even discharge provides a non-dispersing application of the agent. The applicator may be quickly detached to provide a straight stream of chemical where greater range, a narrow discharge pattern or a lobbing effect is required.

(Temperature Range -40°F to 120°F)

SPECIFICATIONS	CLASS D Dry Powder	
	Sodium Chloride	Copper
Powder Type	Sodium Chloride	Copper
Application	Hose & Nozzle or Applicator	
Model Number	B570	B571
Size & Capacity (lbs.)	30	
Shipping Wt. (lbs.)	53	
Height (in.)	32	
Width (in.)	13	
Depth (Diam. - in.)	8	
Range (ft.) with Applicator	3 - 6	
Range (ft.) with Nozzle	8 - 10	
DischargeTime (Sec.) - Applicator	24	18
DischargeTime (Sec.) - Nozzle	13	
F. M. Approved	Yes	
Standard Bracket	Wall	

Stored Pressure



**MODELS
B570
B571**



**FOR COMBUSTIBLE
METAL FIRES**

MODEL B570 contains a special blended Sodium Chloride based dry powder extinguishing agent. Heat from the fire causes it to cake and form a crust excluding air and dissipating heat from burning metal. Metal fires involving magnesium, sodium, potassium and sodium-potassium alloys can be successfully extinguished with this extinguisher. There is data showing that zirconium, uranium, titanium, and powdered aluminum fires can be controlled and extinguished with this unique extinguisher.

Available in 150 lb. Wheeled or Stationary

MODEL B571 contains a copper extinguishing agent specially developed by the U.S. Navy for fighting lithium and lithium alloy fires. The copper compound smothers the fire and provides an excellent heat sink for dissipating heat. Copper powder has been found to be superior to all other known fire extinguishing agents for lithium.

Available in 250 lb. Wheeled

6 YEAR WARRANTY

ABC Dry Chemical

**Manufactured and Tested to
ANSI/UL Standards
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED AND USCG APPROVED**

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction
- ★ Easy and more economical to maintain and service
- ★ U/L & U.S. Coast Guard Listed
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -65°F to 120°F)

Note: All extinguishers are USCG approved with bracket listed on UL label.

Stored Pressure



ABC or Multi-Purpose extinguishers utilize a specially fluidized and siliconized mono ammonium phosphate dry chemical. It chemically insulates Class A fires by melting at approximately 350°F and coats surface to which it is applied. It smothers and breaks the chain reaction of Class B fires and will not conduct electricity back to the operator.

Available in Wheeled and Stationary extinguishers.

6 YEAR WARRANTY

SPECIFICATIONS		ABC Dry Chemical									
VALVES	ALUMINUM						BRASS, CHROME PLATED				
Size & Capacity (lbs.)	2 ½	5	5	6	10 Tall	20	5	6	10 Short	10 Tall	20
Application	Nozzle	Hose and Nozzle				Hose and Nozzle					
Model Number	B417 / B417T	B500 / B500T	B402 / B402T	B443	B456	A411	B424	B461	419	B441	423
U/L Rating	1A:10B:C	2A:10B:C	3A:40B:C	3A:40B:C	4A:80B:C	20A:120B:C	2A:10B:C	3A:40B:C	4A:80B:C	4A:80B:C	20A:120B:C
Shipping Wt. (lbs.)	5¼ / 5½	9¼ / 9½	9¼ / 9½	12¼	18	38	10½	13¼	19	19	39
Height (in.)	15½	15¼	15¼	16	20	23¼	15½	16¼	17 5/8	20½	24
Width (in.)	5¼	7¼	7¼	7¼	7¼	10¼	8	8½	9½	8¼	10¼
Depth (Diam. - in.)	3	4¼	4 ¼	5	5	7	4¼	5	6	5	7
Range (ft.)	9 - 15	12 - 18	12 - 18	15 - 21	15 - 21	15 - 21	12 - 18	15 - 21	15 - 21	15 - 21	15 - 21
Discharge Time (Sec.)	10	14	14	14½	20	30	14	14	22	20	30
Available with Chrome Plated Cylinder	YES	YES	YES		YES			YES	YES	YES	
F. M. Approved	YES	YES		YES	YES	YES		YES	YES	YES	YES
Standard Bracket	Wall / Vehicle-Marine			Wall			Wall				

Regular Dry Chemical

**Manufactured and Tested to
ANSI/UL Standards
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED AND USCG APPROVED**

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction
- ★ Easy and more economical to maintain and service
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -65°F to 120°F)

Note: All extinguishers are USCG approved with bracket listed on UL label.

Stored Pressure



REGULAR extinguishers contain a siliconized sodium bicarbonate based dry chemical with free flowing and non-caking additives. Economical Class B & C protection with lower initial cost and recharging. This chemical smothers fires in flammable liquids and pressurized gases and will not conduct electricity back to the operator.

Available in Wheeled and Stationary extinguishers.

6 YEAR WARRANTY

SPECIFICATIONS	REGULAR Dry Chemical								
VALVES	ALUMINUM						BRASS, CHROME PLATED		
Size & Capacity (lbs.)	1	2½	5	5½	10 Tall	20	6	10 Tall	20
Application	Nozzle			Hose and Nozzle					
Model Number	A620T	B403 B403T	B409T	B453	B457	A412	B462	B447	408
U/L Rating	2B:C	10B:C	10B:C	40B:C	60B:C	120B:C	40B:C	60B:C	120B:C
Shipping Wt. (lbs.)	2½	5½	9¼	9½	18	38	13¾	19	39
Height (in.)	10	15½	15¼	15¼	20	23¼	16¼	20½	24
Width (in.)	3½	5¾	5½	7¼	7¾	10¼	8½	8¾	10¼
Depth (Diam. - in.)	2¾	3	4¼	4¼	5	7	5	5	7
Range (ft.)	5 - 8	9 - 15	12 - 18	12 - 18	15 - 21	15 - 21	15 - 21	15 - 21	15 - 21
Discharge Time (Sec.)	10	10	10	14	18	28	14	18	28
Available with Chrome Plated Cylinder	Yes	Yes	Yes	Yes	Yes				
F. M. Approved		Yes	Yes		Yes	Yes	Yes	Yes	Yes
Standard Bracket	Vehicle	Vehicle - Marine			Wall				

Purple K Dry Chemical

*Manufactured and Tested to
ANSI/UL Standards
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED AND USCG APPROVED*

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction
- ★ Easy and more economical to maintain and service
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -65°F to 120°F)

Note: All extinguishers are U.S. Coast Guard approved with bracket listed on U.L. label.

Stored Pressure



PURPLE K extinguishers contain specially fluidized and sili-conized potassium bicarbonate dry chemical which is particu-larly effective on Class B flammable liquids and pressurized gases. It is electrically non-conductive. Purple K has been the choice of oil, gas, chemical and utilities industries as the preferred fire fighting agent.

Available in Wheeled and Stationary extinguishers.

6 YEAR WARRANTY

SPECIFICATIONS	PURPLE K Dry Chemical				
	ALUMINUM			BRASS, CHROME PLATED	
VALVES					
Size & Capacity (lbs.)	2 ½	5	20	10 Tall	20
Application	Nozzle	Hose and Nozzle			
Model Number	B410T	B479 B479T	A413	B460	415
U/L Rating	10B:C	30B:C	120B:C	80B:C	120B:C
Shipping Wt. (lbs.)	5½	9½	38	19	39
Height (in.)	15½	15¼	23¼	20½	24
Width (in.)	5¾	7¼	10¼	8¾	10¼
Depth (Diam. - in.)	3	4¼	7	5	7
Range (ft.)	9 - 15	12 - 18	15 - 21	15 - 21	15 - 21
Discharge Time (sec.)	10	12	28	22	28
Available with Chrome Plated Cylinder	Yes	Yes		Yes	
F. M. Approved	Yes		Yes	Yes	Yes
Standard Bracket	Vehicle - Marine		Wall		

High Performance *Dry Chemical*

Stored Pressure

**Manufactured and Tested to
ANSI/UL Standards
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED AND USCG APPROVED**

EXTRA FEATURES:

- ★ Superior Range (Vertical & Horizontal)
- ★ High (240 PSI) Operating Pressure
- ★ Choice of Chemicals
ABC Multi Purpose, Regular, Purple K
- ★ Select *Fast Flow* for:
High Flow Rate
Fast Discharge
Quicker Knockdown
More Operator Protection
- ★ Select Compliance Flow for:
Long Range
Highest U.L. Ratings
- ★ Painted GALVANIZED DRAWN STEEL Cylinders
(The best corrosion protection available anywhere)
- ★ Protective Rubber Foot Rings
- ★ All Metal Valve Construction
- ★ Gauge Guards
- ★ Bar Coded and Bi-lingual Labels
(Temperature Range -65°F to 120°F)

Note: All extinguishers are USCG approved with bracket listed on UL label.



HIGH PERFORMANCE extinguishers are the ultimate choice in fire extinguishers for high hazard, frequent use and extreme environment applications. Economical - less initial cost, lower maintenance costs and greater reliability than cartridge operated extinguishers.

Available in 125 and 250 lb. Wheeled and Stationary extinguishers.

Hot dip galvanized USCG brackets available

12 YEAR WARRANTY

SPECIFICATIONS	HIGH PERFORMANCE - ABC, REGULAR, PURPLE K Dry Chemical														
	FAST FLOW									COMPLIANCE FLOW					
Type	ABC			REGULAR			PURPLE K			ABC			PURPLE K		
Agent	ABC			REGULAR			PURPLE K			ABC			PURPLE K		
Size & Capacity - lbs. (kg)	13.2 (6)	20 (9)	30 (13.6)	20 (9)	30 (13.6)	13.2 (6)	20 (9)	20 (9)	30 (13.6)	13.2 (6)	20 (9)	30 (13.6)	13.2 (6)	20 (9)	30 (13.6)
Model Number	594	581	567	582	568	595	580	584	569	592	564	589	599	566	591
U/L Rating	2A:40B:C	4A:40B:C	4A:40B:C	40B:C	40B:C	40B:C	40B:C	20B:C	40B:C	4A:80B:C	20A:120B:C	20A:160B:C	80B:C	120B:C	160B:C
Shipping Wt. (lbs.)	31	42½	58	42½	58	31	42½	42½	58	31	42½	58	31	42½	58
Height (in.)	17½	24¾	26½	24¾	26½	17½	24¾	24¾	26½	17½	24¾	26½	17½	24¾	26½
Width (in.)	10½	10½	11	10½	11	10½	10½	10½	11	10½	10½	11	10½	10½	11
Depth (Diam. - in.)	7	7	8	7	8	7	7	7	8	7	7	8	7	7	8
Range (ft.)	40-50			40-50			40-50			40-50			40-50		
Discharge Rate (Ave.) (lbs./sec.)	.94	1.20	1.60	1.40	1.76	.94	1.44	2.00	1.88	.59	.65	.95	.61	.67	.81
Discharge Time (sec.)	15	18	21	15	17	15	15	10	16	22	30	34	22	29	34
Standard Bracket	Wall														

Brackets & Accessories

Wall Hanger Brackets



Model 883
Two Point Support Wall
Bracket for Halotron I
Models 397 & 398

Bracket Adapters



16536* 16538* 16537
* Galvanized

Vehicle / Marine and Heavy Duty Vehicle (5 lb.) Brackets

Vehicle / Marine / Aviation Brackets




845 817 818 817S 818S



821 821S 861H 808 846

Heavy Duty Box Type Vehicle Brackets
(Red Brackets are Galvanized)



807 809 812 810G 811G 811 810 810CG (USCG)

10 lb. Wall Strap Type




889 889HB



Heavy Duty Dolly Cart

859

Heavy Duty Rubber Strap Brackets



860 862 864

"I" Beam Brackets Exterior



868 - 6", 8", 10", 12"

Interior



872 - 6" to 8", 10" to 12"

Brackets

Extinguisher Type	Size (Capacity)	Model	Cyl. Diam.	Standard Bracket Part Number & Type	U.S.C.G. Approved	Heavy Duty Bracket or Special Bracket with Metal Straps	Heavy Duty Bracket with Rubber Straps	Use With Model 859 Dolly Cart	
WATER	2½ Gal.	240	7"	1007 Wall	N/A	810	864	Yes	
WATER MIST	1¼ Gal.	B270NM	7"	14315 Wall	N/A	N/A	N/A		
	2½ Gal.	B272NM	7"	14315 Wall	N/A	N/A	N/A		
AFFF FOAM	6 Liter	254	7"	1007 Wall	N/A	810	N/A		
	2½ Gal.	250	7"	1007 Wall	N/A	810	864	Yes	
FFFP FOAM	2½ Gal.	252	7"	1007 Wall	N/A	810	864	Yes	
WET CHEMICAL	6 Liter	B260	7"	1007 Wall	N/A	810	N/A		
	2½ Gal.	B262	7"	1007 Wall	N/A	810	864	Yes	
HALOTRON I	1.4 Lb.	A384T	2 7/8"	845 Vehicle	N/A	N/A	N/A		
	2½ Lb.	B385TS	3"	817 Vehicle	N/A	817S	860		
	5 Lb.	B386T	4¼"	818 Vehicle / Marine	818, 821	818S, 821, 821S, 861H, 807	860		
	5½ Lb.	B394TS	4¼"	818S Aircraft	N/A	818S AIRCRAFT (STANDARD)	N/A		
	11 Lb.	397	6	883 Wall	812	812	862		
	15½ Lb.	398	6	883 Wall	812	812	862		
Halon 1211	1¼ Lb.	A344T	2 7/8"	845 Vehicle	N/A	N/A	N/A		
	2½ Lb.	C352TS	3"	817S Vehicle	N/A	817S AIRCRAFT (STANDARD)	860		
	3 Lb.	C354TS	3"	817S Vehicle	N/A	817S AIRCRAFT (STANDARD)	860		
	5 Lb.	B355T	4¼"	818 Vehicle / Marine	818, 821	818S, 821, 821S, 861H, 807	860		
	9 Lb.	B369	5"	0546 Wall	808, 809	808, 809	862		
	13 Lb.	B371	5"	1007 Wall	809	846, 809	862		
ABC Dry Chemical	17 Lb.	361	7"	0577 Wall	810	810	864	Yes	
	2½ Lb.	B417 / B417T	3"	4834 Wall / 817 V.M.	817	817S	860		
	5 Lb.	B402 / B402T	4 ¼"	1521 Wall / 818 V.M.	818, 821	818S, 821, 821S, 861H, 807	860		
	5 Lb.	B500 / B500T	4 ¼"	1521 Wall / 818 V.M.	818, 821	818S, 821, 821S, 861H, 807	860		
	5 Lb.	B424	4 ¼"	16591 Wall	821	821, 821S, 861H, 807	860		
	6 Lb.	B443	5"	5525 Wall	808, 809	808, 809	862		
	6 Lb.	B461	5"	0546 Wall	808, 809	808, 809	862		
	10 Lb.	419	6"	1007 Wall	812	812	862		
	10 Lb.	B456	5"	0546 Wall	809	846, 809	862		
	10 Lb.	B441	5"	1007 Wall	809	846, 809	862		
	20 Lb.	A411	7"	0577 Wall	810	810	864	Yes	
	20 Lb.	423	7"	0577 Wall	810	810	864	Yes	
REGULAR Dry Chemical	1Lb.	A620T	2 7/8"	845 Vehicle	N/A	N/A	N/A		
	2½ Lb.	B403 / B403T	3"	4834 Wall / 817 V.M.	817	817S	860		
	5 Lb.	B409T	4 ¼"	818 Vehicle/Marine	818, 821	818S, 821, 821S, 861H, 807	860		
	5½ Lb.	B453	4 ¼"	1521 Wall	818, 821	818S, 821, 821S, 861H, 807	860		
	6 Lb.	B462	5"	0546 Wall	808, 809	808, 809	862		
	10 Lb.	B447	5"	1007 Wall	809	846, 809	862		
	10 Lb.	B457	5"	0546 Wall	809	846, 809	862		
	20 Lb.	A412	7"	0577 Wall	810	810	864	Yes	
PURPLE K Dry Chemical	20 Lb.	408	7"	0577 Wall	810	810	864	Yes	
	2½ Lb.	B410T	3"	817 Vehicle/Marine	817	817S	860		
	5 Lb.	B479 / B479T	4 ¼"	1521 Wall / 818 V.M.	818, 821	818S, 821, 821S, 861H, 807	860		
	10 Lb.	B460	5"	1007 Wall	809	846 / 809	862		
	20 Lb.	A413	7"	0577 Wall	810	810	864	Yes	
CARBON DIOXIDE	20 Lb.	415	7"	0577 Wall	810	810	864	Yes	
	5 Lb.	322	5 ½"	0546 Wall	809	809	862		
	10 Lb.	330	7"	0575 Wall	810	810	N/A		
	15 Lb.	331	7"	0575 Wall	810	810	864	Yes	
CLASS D Dry Powder	20 Lb.	332	8"	0577 Wall	811	811	864	Yes	
	HIGH PERFORMANCE Dry Chemical <i>Fast Flow and Compliance Flow</i>	13.2 Lb. (6 Kg)	594 ABC (FF) 592 ABC (CF) 595 PK (FF) 599 PK (CF)	7"	9582 Wall	810 & 810G	810 & 810G	N/A	
		20 Lb. (9 Kg)	581 ABC (FF) 582 REG (FF) 580, 584 PK (FF) 564 ABC (CF) 566 PK (CF)	7"	9582 Wall	810 & 810G	810 & 810G	864 & 874	Yes
30 Lb. (13.6 Kg)		567 ABC (FF) 568 REG (FF) 569 PK (FF) 589 ABC (CF) 591 PK (CF)	8"	9581 Wall	811 & 811G	811 & 811G	864	Yes	
CLASS D Dry Powder	30 Lb.	B570 Sodium Chloride	8"	0577 Wall	N/A	811	864	Yes	
	30 Lb.	B571 Copper	8"	0577 Wall	N/A	811	864	Yes	

All brackets are quality manufactured of steel with a primed and powder coated paint finish. The paint finish assures many years of use and meets the latest U/L salt spray requirements (240 hrs. @ 20% salt solution - ASTM B117).

Wheeled

The largest variety of QUALITY wheeled fire extinguishers available anywhere. All available in a Stationary configuration (except 50 lb. Carbon Dioxide). See *"Wheeled Fire Extinguishers"* brochure for more details.

DRY CHEMICAL STORED PRESSURE



Models 495, 496, 497
50 lb. Dry Chemical



Models 573, 574, 575, 690
HIGH PERFORMANCE
125 / 250 lb. Dry Chemical



Models 488, 489, 490
125/150 lb. Dry Chemical

DRY CHEMICAL NITROGEN CYLINDER OPERATED



Models 450, 451, 452
125/150 lb. Dry Chemical



Models 467, 468, 469
125/150 lb. Dry Chemical



Models 470, 471, 472
125/150 lb. Dry Chemical



Models 491, 492, 493
300/350 lb. Dry Chemical

CLASS D



Model 680 150 lb. Sodium Chloride
Model 681 250 lb. Copper

FOAM



Model 630
33 gal. FFFP Foam

CARBON DIOXIDE



Model 333
50 lb. Carbon Dioxide
Model 334
100 lb. Carbon Dioxide

HALOTRON I™



Models 673, 674, 675
65 lb. / 150 lb.
Halotron I™