



Signalhorn/Vibratone Horns, UL Listed, cUL Listed, CSA Certified, FM Approved

- ◆ NEMA 4 with panel mount gasket kit (K8435666A)
- ◆ NEMA 4X, IP55 with weatherproof backbox (WB)

Operating Temp.  
-54°C to +66°C

HxBxT: 4" x 4" x 2½" (102x102x64)mm, Weight/Gewicht: 0.77kg (net)

Cat.No.	Description	Amps	db 1m	Accessories/Zubehör	
350-012-30	12VAC 50/60Hz	0.90	104	NB -	4" (102x102)mm Square Box
350-024-30	24VAC 50/60Hz	0.90	110	WB -	Weatherproof Alu Housing
350-120-30	120VAC 50/60Hz	0.18	110	SF -	Stamped Surface Plate
350-240-30	240VAC 50/60Hz	0.09	110	FG -	Flush Grille
				FB -	Flush Mounting Box T=73mm
450-012-30	12VDC	0.13	103	FBL -	Flush Mounting Box T=92mm
450-012-31	12VDC	0.50	109	PR -	Projector
450-024-31	24VDC	0.25	109	PR2 -	Double Projector
450-125-30	125VDC	0.05	109	K8435666A-	Gasket Kit
450-250-30	250VDC	0.03	109	KFC1516C	Coil (120VAC only)