



SW = Schlüsselweite / Width Across Flats
 UPE = Verpackungseinheit / Packed

Catalog No.	PG	Cable \varnothing	GL	H	SW	UPE
156.0705	7	2- 5	5	24	14	10
156.0707	7	3- 6.5	5	24	14	10
156.0906	9	2- 6	6	26	17	10
156.0908	9	4- 8	6	26	17	10
156.1107	11	3- 7	6	27	20	10
156.1110	11	5-10	6	27	20	10
156.1309	13.5	5- 9	6.5	28.5	22	10
156.1312	13.5	6-12	6.5	28.5	22	10
156.1612	16	7-12	6.5	29.5	24	10
156.1614	16	10-14	6.5	29.5	24	10
156.2116	21	9-16	7	32	30	10
156.2118	21	13-18	7	32	30	10
156.2920	29	13-20	8	37	40	5
156.2925	29	18-25	8	37	40	5
156.3626	36	20-26	8	43	50	5
156.3632	36	22-32	8	43	50	5

Material: Edelstahl 1.4305
 Stainless Steel

O-Ring: Perbunan

Dichtung: Perbunan
 Sealing

Temperatur: -40°C bis +100°C
 Temp. Range (kurz 120°C)

Ölbeständ.: gut / good
 Oil Resist.

Schutzart: IP 68 - 10 bar
 Protection

Farbe: drehblank
 Color Blank

(available M12x1.5-M40x1.5)