



North American Watertight
Pin and Sleeve Receptacles
(Material: Valox 357)

Listed to UL 1682 and 1686
Certified to CSA Standard C22.2 No. 182.1
IEC Classified to Standards 309-1 & 309-2

Cat# 20A	A	B	C	Cat# 30A	A	B	C	Wiring	Volt AC	Color	Ground
320R4-W	55	32	80	330R4-W	60	50	100	2p3w	125	Yellow	4h
320R6-W	55	32	80	330R6-W	60	50	100	2p3w	250	Blue	6h
320R7-W	55	32	80	330R7-W	60	50	100	2p3w	480	Red	7h
420R12-W	55	32	90	430R12-W	60	50	105	3p4w	125/250	Orange	12h
420R9-W	55	32	90	430R9-W	60	50	105	3p4w	3Ø250	Blue	9h
420R7-W	55	32	90	430R7-W	60	50	105	3p4w	3Ø480	Red	7h
420R5-W	55	32	90	430R5-W	60	50	105	3p4w	3Ø600	Black	5h
520R9-W	55	32	100	530R9-W	60	50	110	4p5w	3ØY120/208	Blue	9h
520R7-W	55	32	100	530R7-W	60	50	110	4p5w	3ØY277/480	Red	7h
520R5-W	55	32	100	530R5-W	60	50	110	4p5w	3ØY347/600	Black	5h