



20A, 30A Plug

Dimensions

= mm

North American Watertight
Pin and Sleeve Plugs
(Material: Valox 357)

Listed to UL 1682 and 1686
Certified to CSA Standard C22.2 No. 182.1
IEC Classified to Standards 309-1 & 309-2

Cat# 20A	A	B	C	Cat# 30A	A	B	C	Wiring	Volt AC	Color	Ground
320P4-W	148	71	9-22	330P4-W	174	94	11-30	2p3w	125	Yellow	4h
320P6-W	148	71	9-22	330P6-W	174	94	11-30	2p3w	250	Blue	6h
320P7-W	148	71	9-22	330P7-W	174	94	11-30	2p3w	480	Red	7h
420P12-W	164	79	9-22	430P12-W	174	94	11-30	3p4w	125/250	Orange	12h
420P9-W	164	79	9-22	430P9-W	174	94	11-30	3p4w	3Ø250	Blue	9h
420P7-W	164	79	9-22	430P7-W	174	94	11-30	3p4w	3Ø480	Red	7h
420P5-W	164	79	9-22	430P5-W	174	94	11-30	3p4w	3Ø600	Black	5h
520P9-W	168	87	11-30	530P9-W	188	101	11-37	4p5w	3ØY120/208	Blue	9h
520P7-W	168	87	11-30	530P7-W	188	101	11-37	4p5w	3ØY277/480	Red	7h
520P5-W	168	87	11-30	530P5-W	188	101	11-37	4p5w	3ØY347/600	Black	5h