



20A, 30A Connector

Dimensions

= mm

North American Watertight
Pin and Sleeve Connectors
(Material: Valox 357)

Listed to UL 1682 and 1686
Certified to CSA Standard C22.2 No. 182.1
IEC Classified to Standards 309-1 & 309-2

Cat# 20A	A	B	C	Cat# 30A	A	B	C	Wiring	Volt AC	Color	Ground
320C4-W	171	81	9-22	330C4-W	195	102	11-30	2p3w	125	Yellow	4h
320C6-W	171	81	9-22	330C6-W	195	102	11-30	2p3w	250	Blue	6h
320C7-W	171	81	9-22	330C7-W	195	102	11-30	2p3w	480	Red	7h
420C12-W	187	88	9-22	430C12-W	195	102	11-30	3p4w	125/250	Orange	12h
420C9-W	187	88	9-22	430C9-W	195	102	11-30	3p4w	3Ø250	Blue	9h
420C7-W	187	88	9-22	430C7-W	195	102	11-30	3p4w	3Ø480	Red	7h
420C5-W	187	88	9-22	430C5-W	195	102	11-30	3p4w	3Ø600	Black	5h
520C9-W	195	97	11-30	530C9-W	210	109	11-37	4p5w	3ØY120/208	Blue	9h
520C7-W	195	97	11-30	530C7-W	210	109	11-37	4p5w	3ØY277/480	Red	7h
520C5-W	195	97	11-30	530C5-W	210	109	11-37	4p5w	3ØY347/600	Black	5h