


5371

Dimensions upon Request.



9550-P

**NEMA Configurations**

This chart shows only the male (plug) configurations.

**Industrial Specification Grade Angle Plugs and Matching Outlets/Receptacles.**

Rugged cord clamps for secure clamp grip that accommodate cord diameters from 5/8" (15.9mm) to 1-3/8" (34.9mm) and do not tear conductor jacket. Made of tough, heavy-duty nylon for long service life. Device feature heavy-sectioned dead-front right-angle. Pressure-clamp terminal design. Terminals accept up to #4 AWG stranded conductors. Four-way positioning front module. Solid brass blades for maximum conductivity. UL Listed (File #13393). UL Test 498 (CSA 42) CSA Certified (File #LR-406) where applicable. Mexican NOM Certified (#057). Flammability, Rated U2. Operating Temperature: -40°C to +65°C.

Plug	Outlet	NEMA	Plug	Outlet	NEMA	Plug	Outlet	NEMA
9530-P	5371	5-30	9550-P	5373	5-50			
9630-P	5372	6-30	9650-P	5374	6-50			
9730-P	9730-A	7-30	9750-P	9750-A	7-50			
9332-P	5207	10-30	9450-P	5206	10-50			
9432-P	278	14-30	9452-P	279	14-50	9462-P	9460-A	14-60
8432-P	8430-A	15-30	8452-P	8450-A	15-50	8462-P	8460-A	15-60
8332-P	8330-A	18-30	8352-P	8350-A	18-50	8362-P	8360-A	18-60