


Alternate Output Connectors:



760 - Standard Plug



D9 - 9 Pin Sub "D"



D15 - 15 Pin Sub "D"



M4 - 4 Pin Molex



M6 - 6 Pin Molex

MIADA-Series Low-Profile Power Supplies

Ideal for Notebook Computer & Other Small Systems

Available +5, 6, 7, 8, 9, 10,
12, 15, 16, 17, 18, 19, 20, 21,
22, 23 & +24V on request.

Compact and extremely lightweight. Wide, 95-250Vac input range. Automatic overload recovery. 115-140% overvoltage protection. Line regulation: $\pm 0.2\%$, load regulation: $\pm 5\%$. UL/CSA/TÜV/CE approved. All models have a 1829mm (6') standard, 3-prong input cable and a 1829mm (6') shielded output cable with barrel connector.

Catalog-Number	Output	Max. Power	net Wgt	UPE/Pack		EDP-No
MI2005-760	+5V, 3.00A	15 Watts	368g	10/1	D	112794
MI2009-760	+9V, 2.40A	22 Watts	368g	10/1	D	112798
MI2612-760	+12V, 2.17A	26 Watts	368g	10/1	D	112800
MI2815-760	+15V, 1.90A	28 Watts	368g	10/1	D	112802
MI2818-760	+18V, 1.56A	28 Watts	368g	10/1	D	112805
MI2824-760	+24V, 1.17A	28 Watts	368g	10/1	D	112811