



**POWER SUPPLY CORDS CHINA**

- ◆ 10 Amp. 250 Volt AC
- ◆ RWV HAR 3 x 1.00mm<sup>2</sup>, 70°C
- ◆ Cord Length 2.5m (±0.1m); approximate Cord Ø 7.1mm; brown, blue, green/yellow
- ◆ CCEE File No's:
  - #PX1: CH0030373.99  
CH0017556.2001A
  - #TC8: CH0049191.2000  
CH0017556.2001A

The plug and socket pattern for use in China is specified in publications GB 2099.1-1996 and GB 1002-1996. The Chinese plug is a 3-wire, grounded plug rated at 10A/250VAC used in Class I applications in China. China requires that plugs, connector couplers, and cable used in the construction of the Chinese cordset be tested and approved by the China Commission for Conformity Certification of Electrical Equipment (CCEE) and must bear the CCEE mark (commonly referred to as the Great Wall Mark).

\*Connector #TC8 IEC 60320 C-13 rated at 10 Amp.

Catalog No.	Color	Description	Wght/ea	UPE/Pack	EDP-No
86517040	Black	Plug #PX1 with Connector #TC8 C-13*	170g	100/10	116527
86517050	Black	Plug #PX1, 2nd End RJ0 50.0/5.0mm	155g	100/10	116528