

Specification Grade Single Short-Strap Receptacles

Straight Blade, Specification Grade, Single Receptacles, with Short Strap, 2 Pole, 3 Wire Grounding, 15A and 20A, 125V and 250V


FEATURES

- Corrosion-resistant, plated steel strap locked in to face and back body to resist pulling away from face/body assembly.
- One-piece brass, triple-wipe power contacts for lasting retention.
- Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.
- Impact-resistant nylon face and thermoplastic back body.
- Internal screw-pressure-plate back wire capable of accepting #14 - #10 AWG solid or stranded copper or copper-clad wire.
- Terminal compartments isolated from each other for positive conductor containment.
- Tri-drive terminal and mounting screws.
- Auto-ground clip assures positive ground.
- Standards: UL498, CSA C22.2 No. 42, Conforms to NEMA WD-1 and WD-6.




Catalog No.	Color*	Description	Weight/ea	VPE/Pack	EDP-No.
5258-I	Ivory	15A / 125V AC, NEMA 5-15R	39 g	100/10	101254
5358-I	Ivory	20A / 125V AC, NEMA 5-20R	39 g	100/10	113400
5658-I	Ivory	15A / 250V AC, NEMA 6-15R	39 g	100/10	116613
5858-I	Ivory	20A / 250V AC, NEMA 6-20R	39 g	100/10	118451


* Further colors available, please request or visit our web site at www.biaonline.com for more informations.




NEMA 5-15R



NEMA 5-20R



NEMA 6-15R



NEMA 6-20R

