

**Explosionproof and Dust-tight Fittings and Accessories**

**EXPLOSIONPROOF AND DUST-TIGHT JUNCTION BOXES  
CLASS I, GROUPS C & D;  
CLASS II, GROUPS E, F & G; NEMA 7 & NEMA 9  
MULTI-HUB BOXES**



XJAB

Designed for general wiring in hazardous locations. For pulling and splicing conductors. Serves as mounting outlets with use of appropriate fixture covers.

Available with dome cover for additional splicing room and mounting of various devices.

**Bodies XJAB, XJAD and XJAX 26 thru 46 have two interior mounting bosses, which can be blind tapped.**

**Bodies XJAC, XJAL and XJAT 26 thru 46 have four interior mounting bosses, which can be blind tapped.**

**All bodies 570 thru 890 have solid back, can be tapped blind.**



XJAC  
(No bottom hub)



XJAD

Catalog Number	Conduit Size (In.)	Standard Pkg. Quantity	Standard Pkg. Weight Lbs.
XJAB-26	1/2	10	9
XJAB-36	3/4	10	10
XJAB-46	1	10	12
XJAB-570	1 1/4	5	25
XJAB-690	1 1/2	4	22
XJAB-890	2	4	23
XJAC-26	1/2	10	9
XJAC-36	3/4	10	10
XJAC-46	1	10	12
XJAC-570	1 1/4	5	26
XJAC-690	1 1/2	4	21
XJAC-890	2	4	23
XJAD-36	3/4	10	9
XJAD-46	1	10	15
XJAL-26	1/2	10	9
XJAL-36	3/4	10	10
XJAL-46	1	10	12
XJAL-570	1 1/4	5	26
XJAL-690	1 1/2	4	21
XJAL-890	2	4	23

**NEMA 4 WATERTIGHT OPTIONAL:**  
Consult factory for availability and/or certifications.



**Compliances**

- NEC Class I, Groups C, D  
Class II, Groups E, F, G
- UL Standard 886 - CSA Standard C22.2 No. 30