

Task Lighting  
Hand Lamps

Fluorescent Hand Lamps



These energy-efficient drop lights use only 25% as much power as a standard incandescent light and operate cooler.

They feature durable, shatter-resistant (in normal use) co-extruded outer lamp shields with no-glare reflectors. 3-prong plug is located in a separate ballast housing. Fluorescent lamps are included. UL Listed (E71937).

- 18/3 SJT cord
- 125V, 60 Hz rated

WARNING: Not for use in hazardous or explosive locations.

NOS. 3X734, 6X971 & 5X409  
Starter switch in handle is recessed to prevent false operation. Includes swivel hook for vertical hanging; Nos. 6X971 and 5X409 are furnished with two "S" hooks for horizontal hanging.

MAGNETIC WORK LIGHT, NO. 5XN02  
Two industrial grade magnetic holders (45-lb. pull) securely grip any ferrous metal surface and swivel to direct light where you need it. Convenient hands-free operation.

Uses: For MRO applications, farm, fleet, automotive aftermarket, workshops, and anywhere else temporary lighting is necessary.

Watts	Cord Length (Ft.)	Replacement Lamp	Brand	Stock No.	Each	Shpg. Wt.
8	25	2V235		3X734		2.7
15	25	1V173		6X971		3.3
15	25	1V173		5XN02		4.5
15	50	1V173		5X409		4.2

Industrial Compact Fluorescent Hand Lamp



Rugged lamp provides cool white light that is ideal for inspection and troubleshooting. Features heavy-duty butyrate shield and sealed NeoTEX® rubber handle with end cap to keep out moisture. Exclusive oval shape prevents rolling to better position light source. Includes a 25-ft., 18/3 SJTOW cord with 3-prong, NEMA 5-15 plug. Lamp included. Meets National

Electric Code 410-42. UL Listed (E59049), CSA Certified (LL85374).

- Rubber diaphragm covers switch, sealing it against dirt and moisture
- Fluorescent ballast is located on the cord, keeping the lamp lightweight and easy to use

WARNING: Not for use in hazardous or explosive locations.

Watts	Lumens	Length (In.)	Model	Stock No.	Each	Shpg. Wt.
13	900	13½	1083-3	4V363		4.4

Hazardous Location Hand Lamps



Specially designed for use in areas where ignitable vapors may be present. UL Listed (E30252) for Class I, Div. I Groups C and D, and Class II, Div. I Groups F and G. No. 4V362 CSA Certified (LR39801); No. 4YJ40 CSA Certified (LR38801). Cord is not included. Supplied with rubber grommets to accommodate 16/3 or 14/3 and types S, SO, ST, SOW, or STO cord. Order SOW 16/3 (No. 2W375); SOW-A 14/3 (No. 2W376) 250-ft. roll cord.

No. 4V362 uses a 100W incandescent rough service lamp (not included). 16.5" overall length. See table for suggested lamp stock number.

No. 4YJ40 includes 26W Double Biax fluorescent lamp. 19" overall length.

- Lightweight nonsparking aluminum construction
- Tempered glass lens
- Completely field serviceable

Type	Wattage	Suggested Lamp Stock No.	Model	Stock No.	Each	Shpg. Wt.
Incandescent	100	2V293	61430	4V362		5.5
Fluorescent	26	2D047	1090HZ	4YJ40		5.5