

EMT FITTINGS STEEL - COMPRESSION CONNECTORS


Applications


- For use to bond EMT conduit to a box or enclosure
- 1/2" to 4" connectors provide concrete-tight connections
- compression connectors are suitable for applications above 600V

Product Features


- All steel construction insures mechanical protection for the raceway
- All components are zinc electro plated for corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation

Compliances

-  - Standard 514B
- C22.2 No. 18



**INSULATED THROAT
CONNECTORS
STEEL**



**UNINSULATED
CONNECTORS
STEEL**

ORDERING INFORMATION - DIMENSIONS

COMPRESSION CONNECTORS - STEEL					
INSULATED THROAT CATALOG NUMBER	UNINSULATED THROAT CATALOG NUMBER	TRADE SIZE	UNIT CTN. QTY.	SHIP CTN. QTY.	UPC BAR CODE
2912	2902	1/2"	50	500	—
2912-8	2902-8	1/2"	1	25	—
2913	2903	3/4"	25	250	—
2913-8	2903-8	3/4"	1	20	—
2914	2904	1"	25	100	—
2914-8	2904-8	1"	1	10	—
2915	2905	1-1/4"	5	25	—
2916	2906	1-1/2"	—	20	—
2918	2908	2"	—	20	—
2960	2940	2-1/2"	—	5	—
2962	2942	3"	—	1	—
2964	2944	3-1/2"	—	1	—
2966	2946	4"	—	1	—