

TWIST-LOCK® Devices

3 Pole, 4 Wire Grounding

20 Ampere, 125/250 Volts, 3Ø 250 and 3Ø 480 Volts AC

Safety-Shroud TWIST-LOCK® System



NEMA L14-20R
20A 125/250V
UL/CSA
2 (1) HP



NEMA L15-20R
20A 3Ø 250V AC
UL/CSA
3 HP



NEMA L16-20R
20A 3Ø 480V AC
UL/CSA
5 HP

Safety-Shroud Twist-Lock Receptacles

Description	Catalog Numbers		
Gray Valox® Angle housing, one gang.	HBL2410AR	HBL2420AR	HBL2430AR
Gray Valox Surface mounting, one gang.	HBL2410SR	HBL2420SR	HBL2430SR
Gray Valox Semi-flush, two gang.	HBL2410SR2	HBL2420SR2	HBL2430SR2

Note: See page B-72 for box mounting application.
Housing and flange gray Valox.



HBL2420AR

IP20 SUITABILITY

Insulgrip Connector Bodies

Description	Catalog Numbers		
Black and white nylon.	HBL2413	HBL2423	HBL2433

Note: Cord clamp range .35"-1.15" (9-29).



NEMA L14-20R
20A 125/250V
UL/CSA



NEMA L15-20R
20A 3Ø 250V AC
UL/CSA



NEMA L16-20R
20A 3Ø 480V AC
UL/CSA



HBL2420SR

IP20 SUITABILITY

Safety-Shroud Twist-Lock Plugs

Description	Catalog Numbers		
Black and white nylon body, white Valox shroud.	HBL2411S	HBL2421S	HBL2431S


Note: Cord clamp range .35"-1.15" (9-29).




NEMA L14-20P
20A 125/250V
UL/CSA
2 (1) HP



NEMA L15-20P
20A 3Ø 250V AC
UL/CSA
3 HP



NEMA L16-20P
20A 3Ø 480V AC
UL/CSA
5 HP



HBL2420SR2


Insulgrip Flanged Inlets

Description	Catalog Numbers		
Nylon casing, back wired.	HBL2415	HBL2425	HBL2435


Notes: Only receptacles and plugs 480V AC or less are HP rated.
All HP ratings are AC only.
For technical information, see page B-83.
HP rating in parentheses is phase to neutral.



NEMA L14-20P
20A 125/250V
UL/CSA



NEMA L15-20P
20A 3Ø 250V AC
UL/CSA



NEMA L16-20P
20A 3Ø 480V AC
UL/CSA



HBL2423



HBL2421S

®Valox is a registered trademark of General Electric Company.

Dimensions in Inches (mm)