

## TWIST-LOCK® Devices

### 3 Pole, 4 Wire Grounding

30 Ampere, 125/250 Volts and 3Ø 250 Volts AC


### Safety-Shroud TWIST-LOCK® System



**HBL2710AR**



**HBL2710SR**



**HBL2710SR2**



**HBL2713**



**HBL2711S**



NEMA L14-30R  
30A 125/250V  
UL/CSA  
2 (2) HP



NEMA L15-30R  
30A 3Ø 250V AC  
UL/CSA  
3 HP

### Safety-Shroud Twist-Lock Receptacles

Description	Catalog Numbers	
Angle housing one gang.	<b>HBL2710AR</b>	<b>HBL2720AR</b>
Surface mounting one gang.	<b>HBL2710SR</b>	<b>HBL2720SR</b>
Semi-flush two gang.	<b>HBL2710SR2</b>	<b>HBL2720SR2</b>

Notes: See page B-72 for box mounting application.  
Housing and flange, gray Valox®.



NEMA L14-30P  
30A 125/250V  
UL/CSA



NEMA L15-30P  
30A 3Ø 250V AC  
UL/CSA


### IP20 SUITABILITY Insulgrip Connector Bodies

Description	Catalog Numbers	
Black and white nylon.	<b>HBL2713</b>	<b>HBL2723</b>

Note: Cord clamp range .35"-1.15" (9-29).



NEMA L14-30P  
**30A 125/250V**  
UL/CSA  
2 (2) HP



NEMA L15-30P  
**30A 3Ø 250V AC**  
UL/CSA  
3 HP


### IP20 SUITABILITY Safety-Shroud Twist-Lock Plugs

Description	Catalog Numbers	
Black and white nylon body, white Valox shroud.	<b>HBL2711S</b>	<b>HBL2721S</b>

Note: Cord clamp range .35"-1.15" (9-29).



NEMA L14-30P  
30A 125/250V  
UL/CSA



NEMA L15-30P  
30A 3Ø 250V AC  
UL/CSA

### Insulgrip Flanged Inlet

Description	Catalog Numbers	
Nylon casing, back wired.	<b>HBL2715</b>	<b>HBL2725</b>

Notes: Only receptacles and plugs 480V AC or less are HP rated.  
All HP ratings are AC only.  
HP rating in parentheses is phase to neutral.  
For technical information, see page B-83.

©Valox is a registered trademark of General Electric Company.

Dimensions in Inches (mm)