


## TWIST-LOCK® Devices

### 3 Pole, 4 Wire Grounding

30 Ampere, 3Ø 480 and 3Ø 600 Volts AC

### Watertight Safety-Shroud TWIST-LOCK® System



UL Listed, CSA Certified to Type 4, 4X, & 12



**IP66**  
SUITABILITY



NEMA L16-30R  
30A 3Ø 480V AC  
UL/CSA  
10 HP



NEMA L17-30R  
30A 3Ø 600V AC  
UL/CSA

### Watertight Safety-Shroud Twist-Lock Receptacles

#### Description

Gray Valox® housing and flange.

#### Catalog Numbers

**HBL2730SW HBL2740SW**

Note: Receptacles only fit boxes listed on page B-72.




### Watertight Safety-Shroud Twist-Lock Connector Bodies

#### Description


Black Valox housing, white Valox clamps.

#### Catalog Numbers

**HBL2733SW HBL2743SW**



NEMA L16-30P  
30A 3Ø 480V AC  
UL/CSA  
10 HP



NEMA L17-30P  
30A 3Ø 600V AC  
UL/CSA

### Watertight Safety-Shroud Twist-Lock Plugs

#### Description

Black Valox housing, white Valox clamps.

#### Catalog Numbers

**HBL2731SW HBL2741SW**



### Watertight Safety-Shroud Twist-Lock Inlets

#### Description

Gray Valox housing and flange.

#### Catalog Numbers

**HBL2735SW HBL2745SW**

Notes: Only receptacles and plugs 480V AC or less are HP rated.

All HP ratings are AC only.

Cord grip range for plugs and connector bodies

.35"-1.15" (9-29), #16-4 Type SJ to #8-4 Type S, SO.

For technical information see page B-84.



### CIRCUIT-LOCK® Unfused Safety-Shroud Mechanical Interlock for Twist-Lock Receptacles

#### Description

Mechanical Interlock accommodates 20A and 30A watertight Safety-Shroud receptacles.

#### Catalog Number

**HBLMITL\***

Note: \*See pages B-64 and B-65 for complete details.

®Valox is a registered trademark of General Electric Company.

Dimensions in Inches (mm)