









Wall Plates

Single Receptacle & Power Outlet Openings

Standard Size Plastic & Metal

Description	Color	Nylon	Thermoset	Metal	
		TradeMaster® Plates	Smooth	Material	Smooth
Single Receptacle Openings					
One Gang 	Ivory White Brown Gray Black Red Light Almond	TP7-I TP7-W TP7 TP7-GRY TP7-BK TP7-RED TP7-LA	SP7-I SP7-W SP7 SP7-GRY SP7-LA	Aluminum Brass Polished Brass 430S/S 302S/S	SA7 SB7 SB7-PB SL7 SS7
Two Gang 	Ivory White Brown		SP72-I SP72-W SP72	302S/S	SS72
Three Gang 				302S/S 302S/S Painted Ivory 302S/S Painted White 302S/S Painted Gray	SS73 SS73-I SS73-W SS73-GRY
Power Outlet Receptacle Openings – One Gang					
 40.5 mm hole for 39.7 mm dia. device – 2 mtg. holes	Ivory White Brown Gray Light Almond	TP720-I TP720-W TP720 TP720-GRY TP720-LA	SP720-I SP720-W SP720 SP720-GRY SP720-LA	302S/S	SS720
 41.3 mm hole for 40.5 mm dia. device – 2 mtg. holes				302S/S	SS721
 44.5 mm hole for 43.7 mm dia. device-2 mtg. holes				302S/S	SS725
 54.0 mm hole for 53.2 mm dia. device – 2 mtg. holes				302S/S	SS723
 54.8 mm hole for 54.0 mm dia. device – 2 mtg. holes	Ivory White Brown Gray Black Light Almond	TP724-I TP724-W TP724 TP724-GRY TP724-BK TP724-LA	384-I 384	Chrome 302S/S	S384-C SS724

These products listed to UL514, Cover Plates for Flush-Mounted Wiring Devices, CSA Certified.