


## HSK-INOX

## Metr.



Material 1.4305 (330 SS)  
 Clamping insert PA (Nylon) (PVDF)  
 Seal Buna-N (FPM)  
 O-Ring Buna-N (FPM)  
 Protection IP 68 – 10 bar (NEMA 6 – 150 PSIG)  
 within the specified clamping range  
 Operation -40 °C – 100 °C (-40 °F – 212 °F)  
 Temperature -35 °C – 150 °C (-31 °F – 302 °F) (FPM)



**EMI upon request**  
**Other types of stainless steel available upon request**

AG	Øk mm	GL mm	H mm	Wrench mm	Number HSK-INOX	Number HSK-INOX-PVDF
M 12 x 1,5	3 - 6,5	5	19	14	1.695.1200.50	1.696.1200.50
M 12 x 1,5	2 - 5	5	19	14	1.695.1200.51	1.696.1200.51
M 16 x 1,5	5 - 10	6	22	22	1.695.1600.50	1.696.1600.50
M 16 x 1,5	3 - 7	6	22	22	1.695.1600.51	1.696.1600.51
M 20 x 1,5	10 - 14	6	23	24	1.695.2000.50	1.696.2000.50
M 20 x 1,5	7 - 12	6	23	24	1.695.2000.51	1.696.2000.51
M 25 x 1,5	13 - 18	7	24	30	1.695.2500.50	1.696.2500.50
M 25 x 1,5	9 - 16	7	24	30	1.695.2500.51	1.696.2500.51
M 32 x 1,5	18 - 25	8	29	41	1.695.3200.50	1.696.3200.50
M 32 x 1,5	13 - 20	8	29	41	1.695.3200.51	1.696.3200.51
M 40 x 1,5	22 - 32	8	35	50	1.695.4000.50	1.696.4000.50
M 40 x 1,5	20 - 26	8	35	50	1.695.4000.51	1.696.4000.51

