


HSK-K-Ex

NPT



Material: PA (Nylon) V0 according to UL 94 **RoHS**
 Seal: Buna-N
 O-Ring: Buna-N
 Protection: IP 68 – 10 bar (NEMA 6 – 150 PSIG) within the specified clamping range
 Operating Temperature: -20°C – 95°C (-4°F – 203°F)
 Colors: grey RAL 7035, black RAL 9005, blue RAL 5012

AG	∅ mm	Ex- Generation	GL mm	H mm	 mm	Number grey	Number black	Number blue
3/8" NPT	4 - 8	ATEX	15	22	22 / 19	1.291.3800.70	1.291.3801.70	1.291.3802.70
3/8" NPT	2 - 6	ATEX	15	22	22 / 19	1.291.3800.71	1.291.3801.71	1.291.3802.71
1/2" NPT	6,5 - 12	ATEX	13	27	24	1.291.1200.70	1.291.1201.70	1.291.1202.70
1/2" NPT	5 - 9	ATEX	13	27	24	1.291.1200.71	1.291.1201.71	1.291.1202.71
1/2" NPT/16	10 - 14	ATEX	13	28	27	1.291.1216.70	1.291.1217.70	1.291.1218.70
1/2" NPT/16	7 - 12	ATEX	13	28	27	1.291.1216.71	1.291.1217.71	1.291.1218.71
3/4" NPT	13 - 18	ATEX	14	31	33	1.291.3400.70	1.291.3401.70	1.291.3402.70
3/4" NPT	9 - 16	ATEX	14	31	33	1.291.3400.71	1.291.3401.71	1.291.3402.71
1" NPT	18 - 25	ATEX	19	39	42	1.291.1000.70	1.291.1001.70	1.291.1002.70
1" NPT	13 - 20	ATEX	19	39	42	1.291.1000.71	1.291.1001.71	1.291.1002.71
1 1/4" NPT	18 - 25	ATEX	16	39	46 / 42	1.291.5400.70	1.291.5401.70	1.291.5402.70
1 1/4" NPT	13 - 20	ATEX	16	39	46 / 42	1.291.5400.71	1.291.5401.71	1.291.5402.71
1 1/2" NPT	22 - 32	ATEX	20	48	53	1.291.6400.70	1.291.6401.70	1.291.6402.70
1 1/2" NPT	20 - 26	ATEX	20	48	53	1.291.6400.71	1.291.6401.71	1.291.6402.71

