

**750**

**Ex Signal Horn**



- Zone 1 and 2
- Signal horn for Ex protected areas
- Fully encapsulated
- Silicone free

**TECHNICAL SPECIFICATIONS:**

<b>Dimensions (D x W x H):</b>	152 mm x 148 mm x 356 mm
<b>Housing:</b>	PC / ABS-Blend
<b>Connection:</b>	Cable 3 m, 2 x 0.75 mm <sup>2</sup>
<b>Fixing:</b>	Bracket mounting, sound outlet facing downwards
<b>Explosion protection:</b>	Ⓔ II 2G EEx m II T5
<b>Approval:</b>	BVS 03 ATEX E 118X

**ORDER SPECIFICATIONS:**

Voltage	24 V =	24 V ~	48 V ~	115 V ~	230 V ~
Voltage range	21,6 V ... 26,4 V	21,6 V ... 26,4 V	37,8 V ... 52,8 V	102,5 V ... 126,5 V (50 Hz)	108 V ... 131 V (60 Hz)
Current consumpt.	350 mA	450 mA	220 mA	205 mA	70 mA
	<b>750 000 55</b>	<b>750 000 65</b>	<b>750 000 66</b>	<b>750 000 67</b>	<b>750 000 68</b>

