

**EMERGENCY SELF CONTAINED**  
**COMPLETE WITH BATTERIES, CHARGER AND ELECTRONIC CONTROLS**

**SERIES 9904**  
**Viking IP65**

Enclosed emergency luminaire with high photometric classification. Featuring injection moulded prismatic polycarbonate lens, secured by stainless steel clips.

**FEATURES:**

- Polyester compression moulded body, glass reinforced (GRP)
- Built in gasket
- Prismatic lens with internal prisms, smooth outer surface, injection moulded with sharp sealing ridges against gasket
- IP65 rated
- Grommets supplied for cable entry at both ends
- Stainless steel toggle clips for lens
- Polycarbonate lens

**OPTIONS:**

- Low loss ballasts
- Fused terminal blocks
- Through wiring provision
- Vandal resistant screws to lock toggle clips




F9904/NS/WP - 1x36W Viking      F9905/NS/WP - 2x36W Viking

Suitable for interior and exterior applications, protected to IP65.

NATA LAB tested. Certificate No.s 120/91 and 121/91

|             |       |                |
|-------------|-------|----------------|
| F9904/NS/WP | 1x36W | Non Maintained |
| F9904/M/WP  | 1x36W | Maintained     |
| F9905/S/WP  | 2x36W | Sustained      |
| F9905/M/WP  | 2x36W | Maintained     |



|                            |     |      | MAXIMUM PERMISSIBLE SPACING FOR EMERGENCY LUMINAIRES |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
|----------------------------|-----|------|--|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| PHOTOMETRIC CLASSIFICATION |     |      | MOUNTING HEIGHT - M                                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
|                            |     |      | 2.1  | 2.4  | 2.7  | 3.0  | 3.3  | 3.6  | 4.0  | 4.5  | 5    | 6    | 7    | 8    | 9    | 10   | 15   | 20   |
| F9904/WP                   | CO  | C100 | 13.4   | 14.3 | 15.2 | 16.0 | 16.8 | 17.5 | 18.4 | 19.4 | 20.4 | 22.1 | 23.5 | 24.8 | 25.8 | 26.7 | 29.1 | 28.4 |
|                            | C90 | C125 | 14.1   | 15.1 | 16.1 | 16.9 | 17.7 | 18.5 | 19.5 | 20.6 | 21.7 | 23.5 | 25.1 | 26.5 | 27.7 | 28.8 | 32.1 | 32.5 |
|                            | CO  | D50  | 18.0   | 18.7 | 19.4 | 20.1 | 20.7 | 21.2 | 21.8 | 22.5 | 23.2 | 24.2 | 24.9 | 25.4 | 25.7 | 25.9 | 23.7 | 15.2 |
| F9905/WP                   | C90 | C100 | 13.4   | 14.3 | 15.2 | 16.0 | 16.8 | 17.5 | 18.4 | 19.4 | 20.4 | 22.1 | 23.5 | 24.8 | 25.8 | 26.7 | 29.1 | 28.4 |

**SERIES 9901**  
**Neptune IP65**


Tough enclosed emergency luminaire with exceptionally high photometric classification. Featuring injection moulded prismatic lens in self extinguishing V2 polycarbonate, secured by plastic clips.

Suitable for interior and exterior applications, protected to IP65.

|             |                              |                          |
|-------------|------------------------------|--------------------------|
| F9901/NS/WP | 1x24W compact PL fluorescent | Prismatic Non Maintained |
|-------------|------------------------------|--------------------------|



F9901/NS/WP - 1x24W Neptune



|                            |     |     | MAXIMUM PERMISSIBLE SPACING FOR EMERGENCY LUMINAIRES |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
|----------------------------|-----|-----|--|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| PHOTOMETRIC CLASSIFICATION |     |     | MOUNTING HEIGHT - M                                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
|                            |     |     | 2.1  | 2.4  | 2.7  | 3.0  | 3.3  | 3.6  | 4.0  | 4.5  | 5    | 6    | 7    | 8    | 9    | 10   | 15   | 20   |
| F9901/NS/WP                | CO  | D80 | 21.1   | 22.0 | 22.8 | 23.6 | 24.3 | 25.0 | 25.8 | 26.7 | 27.5 | 28.9 | 30.0 | 30.9 | 31.6 | 32.1 | 32.4 | 28.9 |
|                            | C90 | C80 | 12.7   | 13.5 | 14.4 | 15.1 | 15.8 | 16.5 | 17.3 | 18.3 | 19.1 | 20.7 | 22.0 | 23.0 | 23.9 | 24.7 | 26.1 | 24.0 |